Report Date: 06/07/2011 1 / 6
REVISION DATE 06/07/2011 SDS No. 16508

# SAFETY DATA SHEET PANEL WIPE

# 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME PANEL WIPE
CAS-NO. 64742-49-0
EU INDEX NO. 649-328-00-1
EC (EINECS) NO. 265-151-9

PRODUCT NO. NPW005, PWD005, PWD250

INTERNAL ID C

APPLICATION Cleaning agent

#### **2 HAZARDS IDENTIFICATION**

Highly flammable. Vapours may cause drowsiness and dizziness. Harmful: may cause lung damage if swallowed. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION (1999/45) Xn;R65. Xi;R38. F;R11. N;R51/53. R67.

#### **ENVIRONMENT**

The product contains a substance which is toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

#### **HUMAN HEALTH**

See section 11 for additional information on health hazards.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
NAPHTHA (PETROLEUM),	265-151-9	64742-49-0	60-100%	Xn;R65. Xi;R38. F;R11. N;R51/53.
HYDROTREATED LIGHT				R67.

The Full Text for all R-Phrases is Displayed in Section 16

EU INDEX NO. 649-328-00-1 EC (EINECS) NO. 265-151-9 CAS-NO. 64742-49-0

# **COMPOSITION COMMENTS**

The data shown are in accordance with the latest EC Directives.

# **4 FIRST-AID MEASURES**

# **GENERAL INFORMATION**

Remove affected person from source of contamination. Get medical attention immediately!

# INHALATION

Move injured person into fresh air immediately. Call an ambulance. Be aware that symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Bring these instructions. Place unconscious person on the side in the recovery position and ensure breathing can take place.

### **INGESTION**

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and bring along these instructions.

# SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Consult a physician for specific advice. Burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

# PANEL WIPE

SDS No. 16508

#### **EYE CONTACT**

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Immediately transport to hospital or eye specialist.

#### **5 FIRE-FIGHTING MEASURES**

# **EXTINGUISHING MEDIA**

Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

No specific fire fighting procedure given.

SPECIFIC HAZARDS

In case of fire, toxic and corrosive gases may be formed.

PROTECTIVE MEASURES IN FIRE

Leave danger zone immediately.

#### **6 ACCIDENTAL RELEASE MEASURES**

#### PERSONAL PRECAUTIONS

For personal protection, see section 8. In case of spills, beware of slippery floors and surfaces.

#### **ENVIRONMENTAL PRECAUTIONS**

The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

#### SPILL CLEAN UP METHODS

For waste disposal, see section 13. When dealing with a spillage, please consult the section relating to suitable protective measures. Provide ventilation and confine spill. Do not allow runoff to sewer. Absorb spillage with non-combustible, absorbent material. Contact Health and Safety department on 6147 or 6695 for further assistance.

# 7 HANDLING AND STORAGE

# **USAGE PRECAUTIONS**

Read and follow manufacturer's recommendations. Always remove grease with soap and water or skin cleaning agent, never use organic solvents. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product.

#### STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Store in tightly closed original container in a dry, cool and well-ventilated place.

STORAGE CLASS

Flammable liquid storage.

#### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### PROTECTIVE EQUIPMENT







### PROCESS CONDITIONS

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station.

#### **ENGINEERING MEASURES**

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

# RESPIRATORY EQUIPMENT

Wear suitable respiratory protection. Check that mask fits tight and change filter regularly.

Report Date: 06/07/2011 3 / 6
REVISION DATE 06/07/2011 SDS No. 16508

# **PANEL WIPE**

#### HAND PROTECTION

The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Protection against this substance requires special consideration.

#### **EYE PROTECTION**

Wear tight-fitting goggles or face shield.

#### OTHER PROTECTION

Provide eyewash station. AVOID ALL SKIN AND RESPIRATORY CONTACT!

#### HYGIENE MEASURES

Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet.

#### SKIN PROTECTION

Protection suit must be worn.

#### 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Liquid

COLOUR Clear Colourless
ODOUR Mild Hydrocarbon

SOLUBILITY Immiscible with water Miscible with: Organic solvents.

BOILING POINT (°C) 105 - 135°C 760 mm Hg

RELATIVE DENSITY 0.710 g/cm³ 15°C

BULK DENSITY 710 kg/m3
VAPOUR PRESSURE 4.2 kPa 20°C

FLASH POINT (°C) 11°C CC (Closed cup).

AUTO IGNITION 283°C

TEMPERATURE (°C)

FLAMMABILITY LIMIT - 0.8

LOWER(%)

FLAMMABILITY LIMIT - 6.5

UPPER(%)

# 10 STABILITY AND REACTIVITY

#### **STABILITY**

No particular stability concerns.

**CONDITIONS TO AVOID** 

Avoid heat, flames and other sources of ignition.

HAZARDOUS POLYMERISATION

Will not polymerise.

MATERIALS TO AVOID

Strong oxidising substances. Strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

# 11 TOXICOLOGICAL INFORMATION

INHALATION

Vapours may cause drowsiness and dizziness.

**INGESTION** 

Harmful: may cause lung damage if swallowed.

SKIN CONTACT

Irritating to skin.

**EYE CONTACT** 

May cause temporary eye irritation.

REVISION DATE 06/07/2011 SDS No. 16508

# **PANEL WIPE**

#### **HEALTH WARNINGS**

This chemical can be hazardous when inhaled and/or touched. This chemical may cause skin/eye irritation and burns (corrosive). May cause severe internal injury. Vapour from this chemical can be hazardous when inhaled.

**ROUTE OF ENTRY** 

Inhalation. Ingestion. Skin and/or eye contact. Skin absorption.

# 12 ECOLOGICAL INFORMATION

#### **ECOTOXICITY**

The product contains a substance which is toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

LC 50, 96 Hrs, FISH mg/l 1 - 10 mg/l EC 50, 48 Hrs, DAPHNIA, <10 mg/l

mg/l

IC 50, 72 Hrs, ALGAE, mg/l <10 mg/l

**MOBILITY** 

The product has poor water-solubility.

**BIOACCUMULATION** 

No data available on bioaccumulation.

**DEGRADABILITY** 

The product is easily biodegradable.

#### 13 DISPOSAL CONSIDERATIONS

# **GENERAL INFORMATION**

When handling waste, consideration should be made to the safety precautions applying to handling of the product. Only experts should be permitted to carry out disposal of this material.

# **DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

### 14 TRANSPORT INFORMATION

**GENERAL** 

Full protective clothing should be worn when handling this product.



PROPER SHIPPING NAME PETROLEUM DISTILLATES, N.O.S., or PETROLEUM PRODUCTS, N.O.S.

(NAPHTHA (PETROLEUM), HYDROTREATED LIGHT)

UN NO. ROAD 1268 ADR CLASS NO. 3

ADR CLASS Class 3: Flammable

liquids.

ADR PACK GROUP Ш **TUNNEL RESTRICTION** (D/E)

CODE

HAZARD No. (ADR) 33 ADR LABEL NO. 3 HAZCHEM CODE 3YE UN NO. SEA 1268 **IMDG CLASS** 3 IMDG PACK GR. Ш

Report Date: 06/07/2011 5 / 6
REVISION DATE 06/07/2011 SDS No. 16508

# **PANEL WIPE**

EMS F-E, S-E UN NO. AIR 1268
AIR CLASS 3
AIR PACK GR. II

# 15 REGULATORY INFORMATION

#### **LABELLING**







Harmful

Highly Flammable

Dangerous for the environment

CONTAINS NAPHTHA (PETROLEUM), HYDROTREATED LIGHT

**RISK PHRASES** 

R11 Highly flammable.
R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.
R67 Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S2 Keep out of the reach of children.

S9 Keep container in a well-ventilated place.

Keep away from food, drink and animal feeding stuffs.Keep away from sources of ignition - No smoking.

S24 Avoid contact with skin.

S29/56 Do not empty into drains, dispose of this material and its

container at hazardous or special waste collection point.

S37 Wear suitable gloves.

S46 If swallowed, seek medical advice immediately and show this

container or label.

Use only in well-ventilated areas.

S61 Avoid release to the environment. Refer to special

instructions/safety data sheets.

S64 If swallowed, rinse mouth with water (only if the person is

conscious).

#### **EU DIRECTIVES**

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

# **16 OTHER INFORMATION**

#### **REVISION COMMENTS**

NOTE: Lines within the margin indicate significant changes from the previous revision.

**ISSUED BY** 

Health & Safety Department

REVISION DATE 06/07/2011

Report Date: 06/07/2011 6 / 6
REVISION DATE 06/07/2011 SDS No. 16508

**PANEL WIPE** 

REV. NO./REPL. SDS 10

**GENERATED** 

RISK PHRASES IN FULL

R65 Harmful: may cause lung damage if swallowed.

R11 Highly flammable.
R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R67 Vapours may cause drowsiness and dizziness.

#### **DISCLAIMER**

The information provided in this document has been compiled on the basis of our current knowledge and is believed to be in accordance with the requirements of the Dangerous Substances Directive, Dangerous Preparations Directive and Safety Data Sheets Directive. The information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. The conditions and extent of storage and use of material are outside of our control and within the control of the possessor or user. Consequently it is the responsibility of the possessor or user to satisfy themselves as to the completeness of such information and the suitability of the material for their own particular circumstances, conditions or use.