

121700A Paired - Category 5e DataTuff® Twisted Pair Cable

 	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> <p>Related Documents : No. 8 for DataTwist Cables (Modified Western Electric).pdf</p>
--	--

Description:

24 AWG Bonded-Pairs solid bare copper conductors, polyolefin insulation, PVC inner jacket, rip cord, polyester wrap, aluminum interlocked armor, industrial grade outer PVC jacket. Sequential marking at one meter intervals.

SUITABLE APPLICATIONS:

Suitable Applications	Industrial Ethernet Cable, Harsh Environments, 350MHz Enhanced Category 5e, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, RJ-45 Compatible, Flexible Applications, Armored for Extra Protection
-----------------------	---

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	4
Total Number of Conductors	8
AWG	24
Stranding	Solid
Conductor Diameter	.020 in.
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	PO - Polyolefin
Nom. Insulation Wall Thickness	.009 in.
Insulation Diameter	.035 in.

Pair Color Code Chart :

Number	Color	Number	Color
1	White/Blue Stripe & Blue	3	White/Green Stripe & Green
2	White/Orange Stripe & Orange	4	White/Brown Stripe & Brown

INNER JACKET:

Inner Jacket Material	PVC - Polyvinyl Chloride
Inner Jacket Diameter	.200 in.
Inner Jacket Ripcord	Yes

OVERALL CABLING:

121700A Paired - Category 5e DataTuff® Twisted Pair Cable

Overall Cabling Separator Material	Polyester
------------------------------------	-----------

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:

Outer Jacket Material	Industrial Grade PVC - Polyvinyl Chloride
Outer Jacket Nominal Wall Thickness	.045 in.

ARMORING/OUTER JACKET:

ARMORING :	
Armor Type	Interlocked
Armor Material	Aluminum
Diameter over Armor	.440 in.

OUTER JACKET OVER ARMOR :	
Outer Jacket over Armor (y/n)	Yes
Outer Jacket Material Over Armor	PVC - Polyvinyl Chloride

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	0.530 in.
--------------------------	-----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-40°C To +75°C
Installation Temperature Range	-25°C To +75°C
Bulk Cable Weight	29 lbs/1000 ft.
Max. Recommended Pulling Tension	40 lbs.
Min. Bend Radius (Install)	6.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CM, UL444
CEC/C(UL) Specification	CMG, HL
IEC Specification	11801 Category 5
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
TIA/EIA Specification	568-B.2 Category 5e
Other Specification	NEMA WC-63.1 Category 5e, UL verified to Category 5e

FLAME TEST:

UL Flame Test	UL1685 FT4 Loading
CSA Flame Test	FT4

SUITABILITY:

Sunlight Resistance	Yes
---------------------	-----

121700A Paired - Category 5e DataTuff® Twisted Pair Cable

Oil Resistance Yes

PLENUM/NON-PLENUM:

Plenum (Y/N) N

ELECTRICAL CHARACTERISTICS:

Nom. Mutual Capacitance @ 1 KHz	15 pF/ft
Maximum Capacitance Unbalance (pF/100 m)	66 pF/100 m
Nominal Velocity of Propagation	70 %
Maximum Delay (ns/100 m)	510 ns/100 m
Maximum Delay Skew (ns/100m)	25 ns/100 m
Maximum Conductor DC Resistance @ 20 Deg. C	9 Ohms/100 m
Maximum DCR Unbalance @ 20 Deg. C	3 %
Max. Operating Voltage - UL	300 V RMS

ELECTRICAL CHARACTERISTICS - PREMISE:

Premise Cable Electricals Table 1 :

Frequency (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min. Return Loss (dB)	Min. Structural Return Loss (dB)
1	2.0	65.3	65.3	63.3	63.3	20.0	
4	4.0	56.3	56.3	52.3	52.3	23.0	
8	5.7	51.8	51.8	46.1	46.1	24.5	
10	6.4	50.3	50.3	43.9	43.9	25.0	
16	8.1	47.3	47.3	39.1	39.1	25.0	
20	9.2	45.8	45.8	35.2	35.2	25.0	
25	10.3	44.3	44.3	34.1	34.1	24.3	
31.25	11.6	42.9	42.9	31.3	31.3	23.6	
62.5	16.8	38.4	38.4	21.6	21.6	21.5	
100	21.7	35.3	35.3	17.1	17.1	20.1	
155	27.7	32.5	32.5	4.7	4.7	19.0	
200	32.0	30.8	30.8	3.0	3.0	19.0	
250	36.4	29.3	29.3	>0	>0	18.0	
300	40.5	28.2	28.2	>0	>0	18.0	
310	41.3	27.9	27.9			18.0	
350	44.3	27.2	27.2			17.0	

Premise Cable Electricals Table 2 :

121700A Paired - Category 5e DataTuff® Twisted Pair Cable

Frequency (MHz)	Input (Unfitted) Impedance (Ohms)	Fitted Impedance (Ohms)	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 12	105 ± 10	63.8	60.8
4	100 ± 12	100 ± 10	51.7	48.7
8	100 ± 12	100 ± 10	45.7	42.7
10	100 ± 12	100 ± 10	43.8	40.8
16	100 ± 12	100 ± 10	39.7	36.7
20	100 ± 12	100 ± 10	37.7	34.7
25	100 ± 15	100 ± 10	35.8	32.8
31.25	100 ± 15	100 ± 10	33.9	30.9
62.5	100 ± 15	100 ± 10	27.8	24.8
100	100 ± 15	100 ± 10	23.8	20.8
155	100 ± 18	100 ± 10	19.9	16.9
200	100 ± 20	100 ± 10	17.7	14.7
250	100 ± 20	100 ± 10	15.8	12.8
300	100 ± 20	100 ± 10	14.2	11.2
310	100 ± 20	100 ± 10	13.9	10.9
350	100 ± 22	100 ± 10	12.9	9.9

NOTES:

Notes

US Patent #'s 5, 606, 151; 5, 734, 126 Operating temperatures are subject to length de-rating. Cable passes -40C Cold Bend per UL 1581.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
121700A 0081000	4 PR 24 ARM PVC CABLE	1000	159	GRAY	C Z
121700A 0101000	4 PR 24 ARM PVC CABLE	1000	159	BLACK	C Z
121700A 0103000	4 PR 24 ARM PVC CABLE	3000	459	BLACK	C Z

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 8

Revision Date: 07-12-2006

121700A Paired - Category 5e DataTuff® Twisted Pair Cable

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.