

# **Material Safety Data Sheet**

Copyright, 2002, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This material safety data sheet (MSDS) is provided as a courtesy in response to a customer request. This product is not regulated under, and a MSDS is not required for this product by the OSHA Hazard Communication Standard (29 CFR 1910.1200) because, when used as recommended or under ordinary conditions, it should not present a health and safety hazard. However, use or processing of the product not in accordance with the product's recommendations or not under ordinary conditions may affect the performance of the product and may present potential health and safety hazards.

# SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Adhesive for Hot Melt Fiber Optic Connectors; 6100, 6200, 6300, 8100, 8300

**MANUFACTURER:** 3M

**DIVISION:** Telecom Access Division

**ADDRESS:** 3M Center

St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 09/09/2002 **Supercedes Date:** 12/11/2001

**Document Group:** 09-3272-3

**Product Use:** 

Intended Use: Terminate connectors onto fiber optic cable. Specific Use: Secure optical fiber in fiber optic connector.

# **SECTION 2: INGREDIENTS**

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
POLYAMIDE RESIN	68139-81-1	40 - 70
TERPENE PHENOLIC RESIN	25359-84-6	15 - 40
POLYAMIDE RESIN	68139-78-6	15 - 40

The components of this product are in compliance with the chemical notification requirements of TSCA.

# **SECTION 3: HAZARDS IDENTIFICATION**

## 3.1 EMERGENCY OVERVIEW

Specific Physical Form: MITS data: IN CONNECTOR

\_Page 1 of 7

#### 3M MATERIAL SAFETY DATA SHEET Adhesive for Hot Melt Fiber Optic Connectors; 6100, 6200, 6300, 8100, 8300 09/09/2002

Odor, Color, Grade: BLUE SOLID, MILD RESINOUS ODOR

General Physical Form: Solid

**Immediate health, physical, and environmental hazards:** May cause thermal burns. This product, when used under reasonable conditions and in accordance with the 3M directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the product's directions for use may affect the performance of the product and may present potential health and safety hazards.

### 3.2 POTENTIAL HEALTH EFFECTS

#### **Eye Contact:**

Vapors from heated material may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

### **Skin Contact:**

Thermal Burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction.

#### **Inhalation:**

Vapors from heated material may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, nausea, diarrhea and vomiting.

# **SECTION 4: FIRST AID MEASURES**

## 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Get immediate medical attention.

**Skin Contact:** Immediately flush skin with large amounts of cold water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Cover affected area with a clean dressing. Get immediate medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. If signs/symptoms develop, get medical attention.

# **SECTION 5: FIRE FIGHTING MEASURES**

## 5.1 FLAMMABLE PROPERTIES

Autoignition temperatureNo Data AvailableFlash PointNot ApplicableFlammable Limits - LELNot ApplicableFlammable Limits - UELNot Applicable

## 5.2 EXTINGUISHING MEDIA

Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam). Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

## 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

Unusual Fire and Explosion Hazards: No unusual fire or explosion hazards are anticipated.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Not applicable.

# **SECTION 7: HANDLING AND STORAGE**

# 7.1 HANDLING

For industrial or professional use only.

# 7.2 STORAGE

Store away from heat. Store out of direct sunlight.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Use in a well-ventilated area.

# **8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)**

### 8.2.1 Eye/Face Protection

The following eye protection(s) are recommended: Safety Glasses with side shields.

#### 8.2.2 Skin Protection

Avoid skin contact with hot adhesive.

#### **8.2.3 Respiratory Protection**

Avoid breathing of vapors.

### 8.2.4 Prevention of Swallowing

Not an expected route of exposure.

## 8.3 EXPOSURE GUIDELINES

None Established

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Specific Physical Form: MITS data: IN CONNECTOR

Odor, Color, Grade: BLUE SOLID, MILD RESINOUS ODOR

General Physical Form: Solid

**Autoignition temperature** No Data Available **Flash Point** Not Applicable Flammable Limits - LEL Not Applicable Flammable Limits - UEL Not Applicable Not Applicable **Boiling** point **Density** Not Applicable **Vapor Density** Not Applicable Vapor Density Not Applicable Vapor Pressure Not Applicable **Vapor Pressure** Not Applicable

Specific Gravity 0.960 [Ref Std: WATER=1]

pH No Data Available
Melting point No Data Available
Solubility In Water [Details: NIL]

Solubility in Water Nil

Evaporation rateNot ApplicableVolatile Organic CompoundsNot ApplicablePercent volatileNot ApplicableVOC Less H2O & Exempt SolventsNot ApplicableViscosityNo Data Available

# **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

3M MATERIAL SAFETY DATA SHEET Adhesive for Hot Melt Fiber Optic Connectors; 6100, 6200, 6300, 8100, 8300 09/09/2002

Materials and Conditions to Avoid: Not Applicable

Hazardous Polymerization: Hazardous polymerization will not occur.

# **Hazardous Decomposition or By-Products**

Substance	<b>Condition</b>
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified
Oxides of Nitrogen	Not Specified
Toxic Vapor, Gas, Particulate	Not Specified

# **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

# **SECTION 12: ECOLOGICAL INFORMATION**

## ECOTOXICOLOGICAL INFORMATION

Not Applicable

# CHEMICAL FATE INFORMATION

Not Applicable

# **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste Disposal Method: Dispose of waste product in a sanitary landfill.

Since regulations vary, consult applicable regulations or authorities before disposal.

# **SECTION 14:TRANSPORT INFORMATION**

### **ID** Number(s):

80-6111-2753-3, 80-6111-2754-1, 80-6111-2755-8, 80-6111-2756-6, 80-6111-2757-4, 80-6111-2758-2, 80-6111-2762-4, 80-6111-2763-2, 80-6111-2764-0, 80-6111-2765-7, 80-6111-2766-5, 80-6111-2767-3, 80-6111-2768-1, 80-6111-2769-9,

### 3M MATERIAL SAFETY DATA SHEET Adhesive for Hot Melt Fiber Optic Connectors; 6100, 6200, 6300, 8100, 8300 09/09/2002

2770-7, 80-6111-2771-5, 80-6111-2772-3, 80-6111-2773-1, 80-6111-2774-9, 80-6111-2775-6, 80-6111-4626-9, 80-6111-4965-1, 80-6111-4966-9, 80-6111-4982-6, 80-6111-4983-4, 80-6111-4988-3, 80-6111-6170-6, 80-6111-6276-1, 80-6111-6277-9, 80-6111-6710-9, 80-6111-6953-5, 80-6111-7360-2, 80-6111-7612-6

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

# **SECTION 15: REGULATORY INFORMATION**

### US FEDERAL REGULATIONS

### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

## STATE REGULATIONS

### CHEMICAL INVENTORIES

### INTERNATIONAL REGULATIONS

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: OTHER INFORMATION**

### **NFPA Hazard Classification**

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Reason for Reissue:** Add part numbers 80-6111-4965-1, 80-6111-4966-9, 80-6111-4982-6, 80-6111-4983-4, 80-6111-4988-3. Update MSDS from Prism 8 part to CDMS 16 part.

No revision information is available.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com