

TrueNet®

CopperTen® Dynamic Angle Right/Left Patch Panels



An integral part of ADC's TrueNet® Structured Cabling System, CopperTen® is the world's first UTP structured cabling system to enable 10 Gigabit Ethernet over a full 100 meters. The TrueNet CopperTen dynamic angle right/left patch panel optimizes 10 Gb/s transmission performance, which meet the performance requirements for TIA/EIA 568B.2-10 and ISO/IEC 11801 Class E Ed. 2.1 standards.

The new CopperTen Dynamic Angled Patch Panels allows ADC to deliver the next generation of 10 G performance and take the next leap in angling solutions for the data center and LAN environment while meeting all of the requirements for Augmented Category 6. This new design is available in a 1 RU 24-port and 2 RU 48-port patch panel solution which includes multiple labeling options that allow for use of adhesive, paper label and ID tabs.

Features:

- Patented angle right/left eases stress on patch cords and allows for optimal cable management
- Panel can be used in the flat or angle, silk screen or fascia format for flexible labeling.
- 45 degree silver-plated IDC's provide secure, reliable gas-tight connection
- Universal wiring label for easy termination of either T568A/B
- 110 tool for wire termination
- Rear wire manager included
- UL 1863 Listed and Category 6A performance verified
- 20 year product and zero bit error warranty

SPEC SHEET



www.adc.com • +1-952-938-8080 • 1-800-366-3891

Specifications

MECHANICAL

RJ SOCKET, 8 POSITIONS

General Specification:	FCC Part 68.500 (IEC 603-7)
Operating Temperature Range:	-40° to 70 ° C (-40° to 158 ° F)
Transmission Performance and Reliability:	≥ EIA/TIA 568-B.2-10 and ISO 11801 Class EA
Number of Plug Insertion Cycles:	≥ 750 (IEC/EN 60603-7)

LSA-PLUS® INSULATION DISPLACEMENT WIRE DIAMETER RANGE FOR SOLID AND 22-24 AWG

Stranded Copper Conductors:	0.50 mm to 0.65 mm (0.016" to 0.025")
Wire Insulation Diameter Range (PE,PVC):	1.04 mm to 1.60 mm (0.041" to 0.063")
Contact Resistance:	≤ 1 mΩ typical
Contact Re-terminations:	≥ 200
Insulation Resistance at 40 °C (104 °F) and 93% RH:	≥ 500 mΩ (IEC 512-2-3a)

ENVIRONMENTAL AND SAFETY

Safety compliance:	UL 1863
Flammability rating:	UL 94 V-0

Ordering Information

Description	Catalog Number
24-port Dynamic Angled 1RU UTP patch panel	PP24AC6AT
48-port Dynamic Angled 2RU UTP patch panel	PP48AC6AT

SPEC SHEET



Website: www.adc.com

From North America, Call Toll Free: 1-800-366-3891 • Outside of North America: +1-952-938-8080
Fax: +1-952-917-3237 • For a listing of ADC's global sales office locations, please refer to our website.

ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101
Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

107090AE 4/09 Original © 2008 ADC Telecommunications, Inc. All Rights Reserved