


## 1872A Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable



For more Information  
please call

1-800-Belden1



### Description:

23 AWG bonded-pairs, solid bare copper conductor, non-plenum, polyolefin insulation, rip cord, see color code chart (below), PVC jacket (blue, red, yellow, orange, green, gold, purple, white, black or gray..

### Usage (Overall)

**Suitable Applications:** Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422, Noisy Environments

### Physical Characteristics (Overall)

#### Conductor

**AWG:**

# Pairs	AWG	Stranding	Conductor Material
4	23	Solid	BC - Bare Copper

#### Insulation

**Insulation Material:**

Insulation Material
PO - Polyolefin

#### Outer Shield

**Outer Shield Material:**

Outer Shield Material
Unshielded

#### Outer Jacket

**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

**Outer Jacket Ripcord:** Yes

#### Overall Cabling

**Overall Nominal Diameter:** 9.271 x 4.191 mm

#### Pair

**Pair Color Code Chart:**

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

### Mechanical Characteristics (Overall)

**Operating Temperature Range:** -20°C To +80°C

**Bulk Cable Weight:** 43.158 Kg/Km

**Max. Recommended Pulling Tension:** 200.169 N

**Min. Bend Radius (Install)/Minor Axis:** 25.400 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMR, UL444
CEC/C(UL) Specification:	CMR
Other Standards:	11801 Category 5
EU CE Mark:	No
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	568-B.2-1 Category 6
Other Specification:	UL verified to Category 6

#### Flame Test

UL Flame Test:	UL1666 Riser
CSA Flame Test:	FT4

#### Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	1874A

### Electrical Characteristics (Overall)

#### Nom. Mutual Capacitance:

Capacitance (pF/m)  
49.215

Maximum Capacitance Unbalance (pF/100 m): 49.2

#### Nominal Velocity of Propagation:

VP (%)  
70

#### Maximum Delay:

Delay (ns/100 m)  
510 @ 100MHz

#### Max. Delay Skew:

Delay Skew (ns/100 m)  
25

#### Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)  
9

#### Max. Operating Voltage - UL:

Voltage  
300 V RMS

#### Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)  
3

## 1872A Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable

### Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min RL (dB)
1	1.9	74.3	72.3	70	70	20.0
4	3.7	65.3	63.3	59	59	23.0
8	5.3	60.3	58.8	53	53	24.5
10	5.9	59.3	57.3	51	51	25.0
16	7.5	56.3	54.3	46	46	25.0
20	8.4	54.8	52.8	44	44	25.0
25	9.5	53.4	51.4	42	42	24.3
31.25	10.6	51.9	49.9	39	39	23.6
62.5	15.4	47.4	45.4	30	30	21.5
100	19.8	44.3	42.3	25	25	21.0
155	25.1	41.5	39.5	14	14	21.0
200	29.0	39.8	37.8	10	10	21.0
250	32.8	38.3	36.3	3	3	18.0
300	35.2	37.2	34.2	0	0	18.0
310	37.1	36.9	34.9			18.0
350	39.8	36.2	34.2			17.0
400**	43.0	35.3	33.3			14.0
500**	49.0	33.8	31.8			14.0

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 12	100 ± 15	67.8	64.8
4	100 ± 12	100 ± 15	55.7	52.8
8	100 ± 12	100 ± 15	49.7	46.7
10	100 ± 12	100 ± 15	47.8	44.8
16	100 ± 12	100 ± 8	43.7	40.7
20	100 ± 12	100 ± 8	41.7	38.7
25	100 ± 15	100 ± 8	39.8	36.8
31.25	100 ± 15	100 ± 8	37.9	34.9
62.5	100 ± 15	100 ± 8	31.8	28.9
100	100 ± 15	100 ± 8	27.8	24.8
155	100 ± 15	100 ± 8	23.9	20.9
200	100 ± 15	100 ± 8	21.7	18.8
250	100 ± 20	100 ± 8	19.8	16.8
300	100 ± 20	100 ± 8	18.2	15.2
310	100 ± 20	100 ± 8	17.9	14.9
350	100 ± 22	100 ± 8	16.9	13.9
400**	100 ± 32	100 ± 8	15.7	12.7
500**	100 ± 32	100 ± 8	13.8	10.8

### Notes (Overall)

**Notes:** Belden IBDN. Jacket sequentially marked at 2 ft. intervals. US Patent #'s 5, 606, 151; 5, 734, 126; 5, 821, 467 \*\*Values above 350 MHz are information only. Third party verified to TIA/EIA-568-B.2-1, Category 6.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1872A F6HA1000	305 MT	16.329 KG	GRAY, DARK PEARL		4 PR #23 PP PVC
1872A F6H1000	305 MT	15.876 KG	GRAY, DARK PEARL	C	4 PR #23 PP PVC
1872A X6GA1000	305 MT	16.329 KG	GOLD X6G		4 PR #23 PP PVC
1872A X6G1000	305 MT	15.876 KG	GOLD X6G	C	4 PR #23 PP PVC
1872A 002A1000	305 MT	16.329 KG	RED		4 PR #23 PP PVC
1872A 0021000	305 MT	15.876 KG	RED	C	4 PR #23 PP PVC
1872A 003A1000	305 MT	16.329 KG	ORANGE		4 PR #23 PP PVC
1872A 0031000	305 MT	15.876 KG	ORANGE	C	4 PR #23 PP PVC
1872A 004A1000	305 MT	16.329 KG	YELLOW		4 PR #23 PP PVC
1872A 0041000	305 MT	15.876 KG	YELLOW	C	4 PR #23 PP PVC

## METRIC MEASUREMENT VERSION

### 1872A Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable

1872A 005A1000	305 MT	16.329 KG	GREEN, DARK		4 PR #23 PP PVC
1872A 0051000	305 MT	15.876 KG	GREEN, DARK	C	4 PR #23 PP PVC
1872A 006A1000	305 MT	16.329 KG	BLUE, LIGHT		4 PR #23 PP PVC
1872A 0061000	305 MT	15.876 KG	BLUE, LIGHT	C	4 PR #23 PP PVC
1872A 007A1000	305 MT	16.329 KG	VIOLET		4 PR #23 PP PVC
1872A 0071000	305 MT	15.876 KG	VIOLET	C	4 PR #23 PP PVC
1872A 009A1000	305 MT	16.329 KG	WHITE		4 PR #23 PP PVC
1872A 0091000	305 MT	15.876 KG	WHITE	C	4 PR #23 PP PVC
1872A 0101000	305 MT	15.876 KG	BLACK	C	4 PR #23 PP PVC

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 08-22-2008

© 2010 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.