

## 1403A Multi-Conductor - Small Computer System Interface



For more Information  
please call

1-800-Belden1



### Description:

SCSI, 28 AWG stranded (7x36) TC conductors, non-plenum, flame-retardant polyolefin insulation, polypropylene buffer layer, twisted pairs, overall Beldefoil® shield + TC braid shield (85% coverage), see color code chart (below), light gray PVC jacket.

### Usage (Overall)

**Suitable Applications:** SCSI 2

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Conductors	# Pairs	AWG	Stranding	Conductor Material
68	34	28	7x36	TC - Tinned Copper

#### Insulation

##### Insulation Material:

Insulation Material
FRPO - Flame Retardant Polyolefin

#### Outer Shield

##### Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	85

#### Outer Jacket

##### Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

#### Overall Cable

**Overall Cabling Separator Material:** Foam Polypropylene Binder Tape

**Overall Nominal Diameter:** 0.480 in.

#### Pair

##### Pair Color Code Chart:

Number	Color
1	White/Blue & Blue/White
2	White/Orange & Orange/White
3	White/Green & Green/White
4	White/Brown & Brown/White
5	White/Gray & Gray/White
6	Red/Blue & Blue/Red
7	Red/Orange & Orange/Red
8	Red/Green & Green/Red
9	Red/Brown & Brown/Red
10	Red/Gray & Gray/Red
11	Black/Blue & Blue/Black
12	Black/Orange & Orange/Black
13	Black/Green & Green/Black

## 1403A Multi-Conductor - Small Computer System Interface

14	Black/Brown & Brown/Black
15	Black/Gray & Gray/Black
16	Yellow/Blue & Blue/Yellow
17	Yellow/Orange & Orange/Yellow
18	Yellow/Green & Green/Yellow
19	Yellow/Brown & Brown/Yellow
20	Yellow/Gray & Gray/Yellow
21	Purple/Blue & Blue/Purple
22	Purple/Orange & Orange/Purple
23	Purple/Green & Green/Purple
24	Purple/Brown & Brown/Purple
25	Purple/Gray & Gray/Purple
26	White & Blue
27	White & Orange
28	White & Green
29	White & Brown
30	White & Gray
31	Red & Blue
32	Red & Orange
33	Red & Green
34	Red & Brown

### Mechanical Characteristics (Overall)

<b>Non-UL Temperature Rating:</b>	-20°C To +60°C
<b>Bulk Cable Weight:</b>	106 lbs/1000 ft.
<b>Max. Recommended Pulling Tension:</b>	180 lbs.
<b>Min. Bend Radius (Install)/Minor Axis:</b>	5 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

<b>NEC/(UL) Specification:</b>	CL2, CM
<b>CEC/C(UL) Specification:</b>	CM
<b>EU CE Mark:</b>	Yes
<b>EU Directive 2000/53/EC (ELV):</b>	Yes
<b>EU Directive 2002/95/EC (RoHS):</b>	Yes
<b>EU RoHS Compliance Date (mm/dd/yyyy):</b>	10/13/2005
<b>EU Directive 2002/96/EC (WEEE):</b>	Yes
<b>EU Directive 2003/11/EC (BFR):</b>	Yes
<b>CA Prop 65 (CJ for Wire &amp; Cable):</b>	Yes
<b>MII Order #39 (China RoHS):</b>	Yes

#### Flame Test

<b>UL Flame Test:</b>	UL1685 UL Loading
-----------------------	-------------------

#### Plenum/Non-Plenum

<b>Plenum (Y/N):</b>	No
----------------------	----

### Electrical Characteristics (Overall)

#### Nom. Characteristic Impedance:

Description	Impedance (Ohm)	Tolerance (Ohms)
Differential TDR	122.000	+38 -7
Single Ended TDR	84.000	± 12

#### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
---------------------

## 1403A Multi-Conductor - Small Computer System Interface

12.7

**Nom. Capacitance Cond. to Other Conductor & Shield:**

Capacitance (pF/ft)  
30

**Nominal Velocity of Propagation:**

VP (%)  
66

**Nominal Delay:**

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Delay (ns/ft)
Pair-to-Pair				.04

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)  
64.9

**Nominal Outer Shield DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)  
1.5

**Max. Attenuation:**

()	Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)
2.3		5		

**Max. Operating Voltage - UL:**

Voltage  
150 V RMS

**Max. Recommended Current:**

Current  
0.5 Amps per conductor @ 25°C

### Related Documents:

No related documents are available for this product

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1403A F2V1000	1,000 FT	136.000 LB	GRAY, DEC	C	34 PR #28 FRPP SH PVC
1403A F2V500	500 FT	71.500 LB	GRAY, DEC	C	34 PR #28 FRPP SH PVC

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 03-18-2009

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.