

## 19364 Portable Cordage - UL/CSA Types: SJO, SJT

 For more Information  
 please call

1-800-Belden1

**Description:**

SJT PVC jacket, shielded, 300V, 60° C shielded, Beldfoil® shield (100% coverage), smooth jacket, 20 AWG drain wire (7x28), UL/CSA listed, international color code: light blue, brown, green/yellow.

**Physical Characteristics (Overall)****Conductor****AWG:**

# Conductors	AWG	Stranding	Conductor Material
3	14	41x30	BC - Bare Copper

**Type of Cordage:** SJT
**Insulation****Insulation Material:**

Insulation Material	Wall Thickness (in.)
PVC - Polyvinyl Chloride	.033

**Outer Shield****Outer Shield Material:**

Outer Shield Trade Name	Outer Shield Material	Coverage (%)
Beldfoil®	Aluminum Foil-Polyester Tape	100

**Outer Shield Drain Wire AWG:**

AWG	Stranding	Drain Wire Conductor Material
20	7x28	TC - Tinned Copper

**Outer Jacket****Outer Jacket Material:**

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	.042

**Overall Cable**
**Overall Cabling Fillers:** Jute
**Overall Cabling Color Code Chart:**

Color
Light Blue
Brown
Green/Yellow

**Overall Nominal Diameter:** 0.402 in.
**Mechanical Characteristics (Overall)**
**UL Temperature Rating:** 60°C
**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**
**NEC/(UL) Specification:** SJT

**CSA Specification:** SJT

**EU CE Mark:** Yes

**EU Directive 2000/53/EC (ELV):** Yes

## 19364 Portable Cordage - UL/CSA Types: SJO, SJT

EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Surface Printing (Overall)

## Electrical Characteristics (Overall)

## Max. Operating Voltage - UL:

Voltage
300 V RMS

## Max. Recommended Current:

Current
18 Amps per conductor @ 25°C
13 Amps per conductor @ 25°C over 50 ft.

Dielectric Withstand Voltage:	2000 V AC Applied For 1 Min.
-------------------------------	------------------------------

## Related Documents:

No related documents are available for this product

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
19364 010250	250 FT	26.250 LB	BLACK	C	3#14 PVC PVC SJT

## Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 09-19-2008

© 2012 Belden, Inc  
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.