

658AFJ Composite - Lock Power, Card Reader, Door Contract, REX Applications

For more Information
please call

1-800-Belden1

**Description:**

3 pr. - 22 stranded (7x30) BC cond., Flamarrest® insul., Beldfoil® shield, drain wire, Flamarrest® jacket;
 10 cond. - 22 AWG stranded (7x30) & 18 AWG (7x26) BC cond., Flamarrest® insul., Beldfoil® shield ,
 drain wire, Flamarrest® jacket with ripcord; overall Flamarrest® jacket.

Usage (Overall)

Suitable Applications: Access Control

Coax

Applicable Specifications and Agency Compliance
Applicable Standards & Environmental Programs

EU CE Mark: Yes

Twisted Pair**Physical Characteristics****Conductor****AWG:**

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
3	22	7x30	BC - Bare Copper	0.030

Insulation**Insulation Material:**

Insulation Trade Name	Insulation Material	Dia. (in.)
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	0.047

Twisted Pair Color Code Chart:

Number	Color	Description
1	Black and Red	Card Reader 1
2	Green and White	Card Reader 2
3	Orange and Brown	Card Reader 3

Individual Shield**Outer Shield****Outer Shield Material:**

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
24	7x32	TC - Tinned Copper

Outer Jacket**Outer Jacket Material:**

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (in.)
0.216

Outer Jacket Color Code Chart:

Number	Color	Description
--------	-------	-------------

658AFJ Composite - Lock Power, Card Reader, Door Contract, REX Applications

1	Orange	Card Reader
---	--------	-------------

Electrical Characteristics

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
60.000

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
33.000

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
16.300

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 13.900 Ohm/1000 ft

Max. Recommended Current:

Description	Current
Card Reader	2

Multi Conductor**Physical Characteristics****Conductor**

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
2	22	7x30	BC - Bare Copper	0.030
4	22	7x30	BC - Bare Copper	0.030
4	18	7x26	BC - Bare Copper	0.047

Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Dia. (in.)	AWG
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	0.047	22
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	0.064	18

Insulation Color Code Chart:

Number	Color	Description
1	Black	Door Contact 1
2	Red	Door Contact 2
3	Black	Rex/Spare 1
4	Red	Rex/Spare 2
5	White	Rex/Spare 3
6	Green	Rex/Spare 4
7	Black	Lock/Power 1
8	Red	Lock/Power 2
9	White	Lock/Power 3
10	Green	Lock/Power 4

Individual Shield**Outer Shield**

Outer Shield Material:

AWG	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)	Description
22	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000	Door Contact
22	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000	Rex/Spare
18	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000	Lock/Power

Outer Shield Drain Wire AWG:

Component	AWG	Stranding	Drain Wire Conductor Material
Door Contact	24	7x32	TC - Tinned Copper
Rex/Spare	24	7x32	TC - Tinned Copper
Lock/Power	20	7x28	TC - Tinned Copper

658AFJ Composite - Lock Power, Card Reader, Door Contract, REX Applications

Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

Outer Jacket Diameter:

Component #	Nom. Dia. (in.)
Door Contact	0.128
Rex/Spare	0.147
Lock/Power	0.188

Outer Jacket Ripcord:

Yes

Outer Jacket Color Code Chart:

Number	Color	Description
1	White	Door Contact
2	Blue	Rex/Spare
3	Gray	Lock/Power

Electrical Characteristics

Nom. Capacitance Conductor to Shield:

Description	Freq. (MHz)	Capacitance (pF/ft)
Door Contact	1.000	99.000
Rex/Spare	1.000	59.000
Lock Power	1.000	76.000

Nom. Capacitance Conductor to Conductor:

Description	Freq. (MHz)	Capacitance (pF/ft)
Door Contact	1.000	55.000
Rex/Spare	1.000	33.000
Lock Power	1.000	42.000

Nom. Conductor DC Resistance:

Description	DCR @ 20°C (Ohm/1000 ft)
Door Contact	16.400
Rex/Spare	16.400
Lock Power	6.500

Nom. Inner Shield DC Resistance:

Description	DCR @ 20°C (Ohm/1000 ft)
Door Contact	15.300
Rex/Spare	15.300
Lock Power	7.300

Max. Operating Voltage - UL:

Voltage
300 V RMS

Max. Recommended Current:

Description	Current
Door Contact	2.2 Amps
Rex/Spare	2.2 Amps
Lock Power	4 Amps

Physical Characteristics (Overall)

Conductor

Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name
Flamarrest®

Overall Cable

Overall Nominal Diameter:

0.463 in.

658AFJ Composite - Lock Power, Card Reader, Door Contract, REX Applications

Mechanical Characteristics (Overall)

Operating Temperature Range:	0°C To +75°C
Bulk Cable Weight:	108 lbs/1000 ft.
Max. Recommended Pulling Tension:	200 lbs.
Min. Bend Radius (Install)/Minor Axis:	4.750 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	05/09/2007
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	NFPA 262 Plenum Flame Test (UL910)(FT6)
----------------	---

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	558AFJ

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
658AFJ 0041000	1,000 FT	115.000 LB	YELLOW		4C18+4C22+3P22+2C22 SHLD FLMST

Revision Number: 1 Revision Date: 06-09-2010

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

658AFJ Composite - Lock Power, Card Reader, Door Contract, REX Applications