Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

AX101886 Modular Connectors - MediaFlex Multimedia insert 1-Port SVGA







For more Information please call

1-800-Belden1



Description:			
MediaFlex Multimedia insert 1-Port SVGA			
Usage (Overall)			
Suitable Applications:	Multimedia		
Related Parts:			
	Compatible with MediaFlex Faceplates		
Physical Characteristics (Connectivity)			
Dimensions Dimensions:			
Height (in.) Width (in.) Depth (in.) 1.390 2.050 1.410			
Materials Materials:			
Description Type Material			
Front Connection SVGA Metal Rear Connection 110			
Insert Plastic - UL94V-0			
Color			
Color:	Almond		
Weight			
Weight:	0.057 lbs.		
Included Parts			
Included Parts:	pin assignment guide		
Packaging			
Packaging:	Individually packaged in a suitable plastic bag.		
Mechanical Characteristics (Connectivity)			
Storage Temperature Range:	-40°C To +70°C		
Installation Temperature Range:	-10°C To +60°C		
Operating Temperature Range:	-10°C To +60°C		
Tool Compatibility:	Connecting Tool (AX100749), Termination Station (AX101852), Release Tool (AX101185)		
Applicable Specifications and Agency Co	npliance (Overall)		
Applicable Standards & Environmental Progra			
EU Directive 2002/95/EC (RoHS):	Yes		
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2006		
MII Order #39 (China RoHS):	EUP 50		
Safety Listing:	ACA, Bi-national (UL/CSA) Standard Listed		
Suitability			
Suitability - Indoor:	Yes - Indoor		

Detailed Specifications & Technical Data





AX101886 Modular Connectors - MediaFlex Multimedia insert 1-Port SVGA

Transmission Characteristics (Connectivity)

Notes (Overall)

Notes: For proper installation refer to pin assignment guide provided with the product and Installation Guide PX102063 available on our web site at http://www.belden.com

Product Family

Part Number List:

Item Number	Color
AX101885	Gray
AX101886	Almond
AX101887	Electrical White
AX101888	Black

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	F	Putup	Ship Weight	Color	Notes	Item Desc
AX101886	1	1 EA	0.058 LB			MEDIAFLEX SVGA IDC INSER

Revision Date: 06-03-2009 **Revision Number: 0**

© 2012 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.