

C601106010A06 Cable Assemblies - 3600 Pre-Terminated Cable Assembly

For more Information
please call

1-800-Belden1

**Description:**

3600 Pre-Terminated Cable Assembly, Bonded-Pair, 4-Pair, 23 AWG Solid, T568A/B-T568A/B, 6 Cables, CMR, Blue, 10 ft. (3.0 m).

Usage (Overall)

Suitable Applications:	IBDN System 3600, TIA Category 6
Related Parts:	CAT6+ RJ45 Couplers, CAT6+ Coupler Patch Panels

Multi Conductor**Physical Characteristics****Conductor****AWG:**

# Pairs	AWG	Stranding	Conductor Material
4	23	Solid	BC - Bare Copper

Insulation**Insulation Material:**

Insulation Material
PO - Polyolefin

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Color Code Chart:

Color
Blue

Overall Cabling

Overall Cabling Fillers:	Cross Web
---------------------------------	-----------

Overall Diameter

Overall Nominal Diameter:	0.750 in.
Individual Cable Diameter:	0.235 in.

Physical Characteristics (Connectivity)**Materials****Materials:**

Description	Type	Material
Plug	RJ45	Polycarbonate
Boot		Rubber
Front Connection	Blades	Phosphor Bronze with 50u inch Gold over Nickel Plating
Sleeve		Engineered Polymer Riser Rated

Color

Boot Color:	Translucent
--------------------	-------------

Wiring Scheme

Wiring Scheme:	T568A/B-T568A/B
-----------------------	-----------------

C601106010A06 Cable Assemblies - 3600 Pre-Terminated Cable Assembly**Weight**

Weight: 3.580 lbs.

Packaging

Packaging: Individually packaged in a box.

Mechanical Characteristics (Connectivity)

Plug / Jack Compatibility: RJ45

Termination Interface:

Termination	Connection	Durabilities
RJ45	Mated Connection	750 Cycles

Storage Temperature Range: -40°C To +70°C

Installation Temperature Range: -10°C To +60°C

Operating Temperature Range: -10°C To +60°C

Max. Recommended Pull Tension: 25 lbs.

Min. Bend Radius (Overall Cable): 1.040 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

UL Rating: Riser

Other Standards: FCC Part 68, Subpart F, IEC 60603-7

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 08/01/2009

MII Order #39 (China RoHS): EUP 50

Telecommunications Standards: Category 6 - TIA 568.C.2, ISO/IEC 11801:2002 Ed.2

Safety Listing: Bi-national (UL/CSA) Standard Listed

Suitability

Suitability - Indoor: Yes

Transmission Characteristics (Connectivity)**Performance Table 1:**

Frequency (MHz)	Max. Insertion Loss TIA* (dB)	Max. Insertion Loss Belden (dB)	Min. PSNEXT TIA* (dB)	Min. PSNEXT Belden (dB)	Min. PSACRF TIA* (dB)	Min. PSACRF Belden (dB)
1.000	2.400	2.000	72.300	77.300	64.800	69.800
4.000	4.500	3.700	63.300	68.300	52.800	57.700
8.000	6.400	5.200	58.800	63.800	46.700	51.700
10.000	7.100	5.800	57.300	62.300	44.800	49.800
16.000	9.100	7.400	54.200	59.300	40.700	45.700
20.000	10.200	8.300	52.800	57.800	38.800	43.700
25.000	11.400	9.300	51.300	56.400	36.800	41.800
31.250	12.800	10.400	49.900	54.900	34.900	39.900
62.500	18.500	15.000	45.400	50.400	28.900	33.800
100.000	23.800	19.300	42.300	47.300	24.800	29.800
200.000	34.800	28.300	37.800	42.800	18.800	23.700
250.000	39.400	32.100	36.300	41.400	16.800	21.800
300.000		35.600		40.200		20.200

Performance Table - Footnote: 100 meter Cable Specifications - * TIA/EIA-568-C.2 Category 6 Standard

Performance Table 2:

Frequency (MHz)	Min. Return Loss TIA* (dB)	Min. Return Loss Belden (dB)	Min. Balanced TCL TIA* (dB)	Min. Balanced TCL Belden (dB)
1.000	20.000	20.000	40.000	42.000

C601106010A06 Cable Assemblies - 3600 Pre-Terminated Cable Assembly

4.000	23.000	23.000	40.000	42.000
8.000	24.500	24.500	40.000	42.000
10.000	25.000	25.000	40.000	42.000
16.000	25.000	25.000	38.000	40.000
20.000	25.000	25.000	37.000	39.000
25.000	24.200	25.000	36.000	38.000
31.250	23.300	25.000	35.100	37.100
62.500	20.700	25.000	32.000	34.000
100.000	19.000	25.000	30.000	32.000
200.000	16.400	21.600	27.000	29.000
250.000	15.600	20.500	26.000	28.000
300.000		20.100		

Dielectric Strength: 1,000 V RMS @ 60 Hz for 1 minute

Current Rating: 1.500 A

Insulation Resistance: 500 M-Ohm Minimum

Max. Contact Resistance: 20 m-Ohm

Labeling

Labeling: Labeled at both ends: Part Number, Serial Number, Termination Scheme, Length, Individual cable identification. Customized Labeling for cable assemblies optional upon request.

Notes (Overall)

Notes: C601106010A06 is subdivided as following C6-01-1-06-010-A-06 where C6 stands for performance, 01 stands for jacket type, 1 stands for termination type, 06 stands for color, 010 stands for length, A stands for assembly, and 06 stands for number of cables Use "010" part of the code to specify length in feet - 006-050 ft in increments of 1 ft - 055-295 ft in increments of 5 ft

Product Family**Product List:**

Description	Black	Blue	White
3600 Pre-Terminated Cable Assembly - CMR	C601100010A06	C601106010A06	C601109010A06
3600 Pre-Terminated Cable Assembly - CMP	C602100010A06	C602106010A06	C602109010A06

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
C601106010A06	1 EA	4.830 LB	BLUE, LIGHT		3600 PRE-TERM ASSY BLU 10FT

Revision Number: 1 Revision Date: 02-22-2010

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.