

Clarity 5E Angled TracJack, T568A/B, 45 degree, Red


OR-TJ5E45-42



Clarity 5E Angled TracJack, ETL verified to TIA Category 5e component specification, is front-loading and front removable. New universal T568A/B wiring label and tapered wiring towers simplify termination. Center tuned to Clarity 5E patch cords for significant performance above Category 5e.

features & benefits

- Angled design: Reduces profile of cord connection.
- ETL Verified to Category 5e component standard: Ensures standards compliance.
- Center tuned design: Transparent interface with Clarity5e cords.
- Easy lace IDC housing: Reduces wiring time.
- Easy-to-follow universal wiring label: Quick, user-friendly, eliminates confusion.



- Standard TracJack footprint: Fits in all TracJack faceplates.
- Icon compatible, with 5E Marking on jack face: Supports 606 designation requirements.
- RoHS compliant: Lead free.

specifications

General Info

Category Performance Application: Category 5e/UTP

Color: Red

Footprint: TracJack Number Of Ports: 1-port

Listing Agencies/Third Party Information

CUL Listing No: E131600 ETL Listing No: 3013270-003 ETL Standard: Yes FCC Standard: Yes UL Listing No: E131600 UL Standard: Yes

Construction Information

Component1: Plastic TracJack Housing

Component2: Array of eight modular dual reactance contacts

Component3: IDC contacts (Low noise)
Component4: Printed circuit board

Finish Plating2: Nickel plating and a minimum of 50 micro inches of selective gold plating in contact area

Finish Plating3: Nickel plating with tin over plate

Material1: High Impact Thermoplastic ABS/polycarbonate 94V-0

Material2: Beryllium Copper Material3: Phosphor bronze

Material4: Two-sided FR-4 epoxy resin/glass base with solder mask

Dimensions

Depth Metric: 31.24 mm Height Metric: 23.37 mm

Height U S: .92"

Width Metric: 18.54 mm

Technical Information

Category Rating: Category 5e Wire Gauge: 22-26 AWG

Buy American Act Compliance

Country of Origin: MEXICO

Buy American Act Status: Trade Agreement Act Compliant