## Technical Data Sheet RG11/U Type CATV Coaxial Cable Plenum





2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420 www.westpenn-wpw.com

PART NUMBER: 25821

**DESCRIPTION:** RG11/U – 1 Conductor 14 AWG Solid, 100% Al. Foil + 65% Al. Braid and an overall Plenum

Jacket.

**NEC RATING:** CATVP/ CL2P

**APPROVALS:** (UL) Listed

**APPLICATION:** Indoor Plenum for:- CATV/MATV

## **Construction Parameters:**

Conductor 14 AWG Bare Copper

Stranding Solid

Insulation Material Gas Injected Polyethylene

Insulation Thickness .280" Nom.

Number of Conductors 1 Center Conductor

Shield 100% Al Foil + 65% Al. Braid

Jacket Material Copolymer

Overall Cable Diameter 0.352" Nom.
Approximate Cable Weight 43 Lbs/1M' Nom.
Flame Rating NFPA 262

## **Electrical & Environmental Properties:** Mhz db/100ft Temperature Rating -20deg C to 60deg C .25 Max.Capacitance Between Conductors @ 1 KHz 16.2 pf/ft Nom. 55 1.00 82% Nom. Velocity of Propagation 100 1.50 Impedance 75 ohms Nom. 270 2.0 DC Resistance per Conductor @ 20deg C 2.6 Ohms/1M' Nom. 400 2.98 Jacket Color Natural 550 3.5 **RoHS Compliant** Yes 750 4.9 5.5 1000 **Mechanical Properties:** 2000 7.5 Max. Recommended Pull Tension 230 lbs. 2250 7.95 Min. Bend Radius (Install) 3.5" 3000 9.19

## **Connectors and Accessories**

F Crimp: CN-F11TFE F Compression: CN-FS11PL

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.