

ETP-400D – Dual Button Emergency/Information Phone

Description


The **ETP-400D** is an outdoor-rated, ADA-compliant hands-free 2-button Emergency/Information Phone for use in locations such as: parking facilities, college campuses, controlled access gates, medical centers and more.

Features

- Two buttons for both Emergency and non-Emergency calls
- Cast metal raised letter and Braille signage for ADA compliance
- Vandal resistant stainless steel faceplate and metal button
- Uses regular phone lines or PBX
- Phone line powered: no power supply or battery back-up needed
- Auxiliary input and outputs to integrate with CCTV, Blue Light Strobe, Scream Alert™ and other devices
- Circuit boards are conformally coated for water protection
- LED indicator for hearing impaired
- Built-in auto-dialer can dial two numbers per button: if first number doesn't answer or is busy, dials second number
- Auto-answer allows security to monitor and initiate calls with Emergency Phone
- Options available that offer the ability to automatically identify attendant of location of calling phone by recorded message and digital display



Specifications


Construction:	12 gauge (2.8mm) #4 brushed stainless steel face plate
Dimensions:	Front Panel: 9.5(241) W x 11.75(298) H in(mm) Wall Opening: 6.63(168) W x 9.75(248) H x 2.5(64) D in(mm)
Weight:	8 lbs. (3.6kg)
Operating Temperature:	-4°F to +149°F (-20°C to +65°C)
Mounting:	Flush mounts (surface mount options available)
Communication:	2-way hands-free communication
Digit Capacity:	Up to 18 digits, including pauses, for each of two phone numbers per button
Dialing Speed:	Approximately 10 tones per second
Power Source:	Phone line powered (requires 20mA at 24 v off-hook)
Connection:	Parallel tip and ring connected to RJ11 connector for quick installation
Circuit Protection:	Varistor lightning suppressed and full wave polarity guarded
Programming:	Non-volatile EEPROM programming can be done from any telephone. No battery back-up is needed
"On Time":	Programmable from 1-4270 minutes in 1-minute increments.
Wiring Requirements:	1 twisted-shielded pair
Compliance:	CSA Certified to UL Standard 60950 

Options & Accessories

Voice Location Identifier:	Model ETP-400DV includes the capability to record a message identifying the location of the call. Message is recorded and duration set during programming.
Faceplate camera:	Add "OP3" to model number to add a color pinhole camera mounted discreetly behind the faceplate. Add "OP3BW" for a b/w camera.
"TO CALL" Casting:	On Model ETP-400DC the top button reads TO CALL instead of EMERGENCY
8-Line Consolidator:	Model EC-8 allows connection of up to 8 phones on one phone line while retaining ability to call each phone individually. Can also create a closed system without need for any phone lines.

ETP-400D – Dual Button Outdoor Emergency/Information Phone

Dimensions



Copyright 2009 Talk-A-Phone Co. All rights reserved.

Talk-A-Phone Co. • 7530 North Natchez Avenue • Niles, Illinois 60714-3804
Phone 773.539.1100 • Fax 773.539.1241 • info@talkaphone.com • www.talkaphone.com
All prices and specifications are subject to change without notice.
Talk-A-Phone, Talk-A-Lert, Scream Alert and WEBS are registered trademarks of Talk-A-Phone Co.