

# Anaerobic Connector Consumables

Neon yellow lapping film, 12 µm, 5-in disk

CORNING

Corning Cable Systems Anaerobic-Cure Connectors offer optical performance in a fast, easy field-termination solution designed for fiber-to-the-workstation applications for single-mode and multimode connections. This connector combines the quick-cure convenience of anaerobic adhesive with the performance of epoxy-and-polish connectors. Ideal for enterprise networks and any installations requiring field-installed connectors, the anaerobic-cure technology enables fiber optic networks to be installed cost effectively with minimal tools. Installation of the connector can be accomplished in minutes with the anaerobic adhesive two-part epoxy process. The adhesive is first injected into the connector ferrule and then the fiber is dipped into the primer and inserted into the connector. Curing takes only one minute without the use of lamps or ovens. With the hand-polish process, an average insertion loss of 0.2 dB is achieved.

## Features and Benefits

### Quick-cure epoxy

No lamps or ovens needed

### Minimal tools and no index-matching gel

Low installation cost

### Hand polished for minimum insertion loss

Reliability and optical performance



Part Number: 2104071-01

## Specifications

### General Specifications

Technology	Field Polish (anaerobic)
Mineral	Aluminum Oxide
Mineral Size	12 µm

### Mechanical Characteristics

Weight	0.02 kg (0.05 lb)
--------	-------------------

CORNING

# Anaerobic Connector Consumables

Neon yellow lapping film, 12 µm, 5-in disk

CORNING

## Polishing Film Specifications

Film Type	Neon Yellow Lapping
Mineral	Aluminum Oxide
Mineral Size	12 µm

## Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

## Ordering Information

Part Number	2104071-01
Product Description	Anaerobic Connector Consumables Lapping Film

## Shipping Information

Units per Delivery	15/1
Package Contents	Polishing Film



Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/cablesystems](http://www.corning.com/cablesystems)

A complete listing of the trademarks of Corning Cable Systems is available at [www.corning.com/cablesystems/trademarks](http://www.corning.com/cablesystems/trademarks).

Corning Cable Systems is ISO 9001 certified. © 2012 Corning Cable Systems. All rights reserved.

CORNING