

Liebert PowerSure® PST

Sensible Power Protection In A Compact Package

The Liebert PowerSure PST is an Off-Line UPS designed for individual desktop protection. The orange outlets provide battery and surge protection for your computer and monitor, while the black outlets protect your printer and scanner from surges. Data-Line protection for Phone / Fax / Internet / DSL / Modem is also provided.

The PST gives you more than enough time to save your files and shutdown your system. With the USB communications, you can shutdown automatically when running Windows 2000, XP or Mac OS X 10.2 (or later).



The PowerSure PST Offers A Variety Of Other Standard Features:

Reliability:

- Lightning and Surge Protection (TVSS)
- Data Line Surge Protection (1 Input/2 Output)
- Full Sequenced Battery Testing
- Advance Early Warning Shutdown

Flexibility:

- Three Battery-Backed UPS Outlets with space for transformer blocks
- Two Surge-Only Outlets
- USB, MicroSoft Windows (XP and 2000) and Mac (OS X version 10.2 or later) Certified

Low Total Cost Of Ownership:

- Two-Year Warranty

The Liebert PowerSure® PST Is Ideally Suited For:

- Desktop PC's
- Workstations
- Other Sensitive Electronics



PowerSure® PST Specifications

Model Number	PA350-120U	PA500-120U
POWER RATING VA/W	350VA/225W	500VA/300W
DIMENSIONS: in. (mm)		
Unit	6.6 x 9.8 x 3.7	
W x D x H	(168 x 250 x 95)	
WEIGHT: lbs (kg)		
Unit	11.7 (5.3)	13.5 (6.1)
INPUT AC PARAMETERS		
Surge Protection	603J	
Voltage Range Without Battery Operation	98VAC - 140VAC ±3VAC	
Input Power Cord	6.5 ft. (2m) attached, w/ NEMA 5-15 P	
OUTPUT AC PARAMETERS		
Output Receptacles	(3) NEMA 5-15R (orange) Battery backup + surge protection; (2) NEMA 5-15R (black) Surge protection	
Voltage (Battery mode)	120VAC ±8%	
Waveform (Battery mode)	Stepped Sinewave	
Frequency	60Hz ±1Hz	

PowerSure® PST Runtime Table

Typical Battery Backup Time	350VA	500VA
Pentium II w/15" Monitor	19 min.	25 min.
Pentium II w/17" Monitor	12 min.	18 min.
Pentium II w/21" Monitor	11 min.	15 min.
Pentium III w/15" Monitor	10 min.	14 min.
Pentium III w/17" Monitor	9 min.	13 min.
Pentium III w/21" Monitor	6 min.	9 min.
Pentium 4 w/15" Monitor	8 min.	11 min.
Pentium 4 w/17" Monitor	6 min.	9 min.
Pentium 4 w/21" Monitor	-	6 min.



Status indicators let you know the condition of the UPS.



All outlets are spaced to accommodate transformer plugs.



USB port offers communication to shut down if an outage ever exceeds battery capacity.



Data-Line protection ensures that your communication outlets (Phone / Fax / DSL / Internet / Modem) are also protected.

Liebert Corporation

1050 Dearborn Drive
P.O. Box 29186
Columbus, Ohio 43229
800 877 9222 Phone (U.S. & Canada Only)
614 888 0246 Phone (Outside U.S.)
614 841 6022 FAX

Via Leonardo Da Vinci 8
Zona Industriale Tognana
35028 Piove Di Sacco (PD)
Italy
39 049 9719 111 Phone
39 049 5841 257 FAX

Emerson Network Power Asia Pacific
7/F., Dah Sing Financial Centre
108 Gloucester Rd, Wanchai
Hong Kong
852 25722201 Phone
852 28029250 FAX

liebert.com

24 x 7 Tech Support

800 222 5877 Phone
614 841 6755 (outside U.S.)

While every precaution has been taken to ensure accuracy and completeness in this literature, Liebert Corporation assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

© 2005 Liebert Corporation. All rights reserved throughout the world. Specifications subject to change without notice.

All names referred to are trademarks or registered trademarks of their respective owners.

© Liebert and the Liebert logo are registered trademarks of the Liebert Corporation.

SL-23277 (R2/06) Printed in USA

Emerson Network Power.

The global leader in enabling business-critical continuity.

- AC Power Systems
- Connectivity
- DC Power Systems
- Embedded Power
- Power Protection
- Integrated Cabinet Solutions
- Outside Plant
- Precision Cooling
- Site Monitoring and Services

EmersonNetworkPower.com

Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co.
©2005 Emerson Electric Co.