THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. DIMENSIONS **WEIGHT PANDUIT** lbs 10 PART NO. **"**B" 7 (7 * A * (g) DCS 2.00 0.74 0.260 4.62 JP4W-___ (18.8)(50.80) (6.60) (2095.0)(REF) SECTION A-A TAK-TY 'B' SLOT (BEND RADIUS CONTROL) 0 7.70 [195.58] (REF) 1.50 R [38.10] (REF) R (TYP) 2.60 6.55 [66.04] [166.37] (REF) (REF) DIMENSIONS IN BRACKETS ARE METRIC [mm] NOTES: CAD FILENAME/LAYERS SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR G03043DC_PB_JP4W_00 PACKAGE SIZE AND PRODUCT COLOR.
MATERIAL: 33% GLASS FILLED NYLON 6/6 PRODUCT IS DESIGNED TO SUPPORT A MAXIMUM 4.0" (101.6) DIAMETER BUNDLE. RECOMMENDED MAXIMUM STATIC LOAD: 100 lbs. PRODUCT INCORPORATES FEATURES ALLOWING USER TO RETAIN CABLE CORP. TINLEY PARK, ILLINOIS BUNDLES IN J-PRO J-HOOK WITH TAK-TY CABLE TIES UP TO 3/4" WIDE. J-PRO J-HOOK PRODUCT MARKINGS: WALL MOUNT cULus logo and statement: "SUITABLE FOR USE IN AIR HANDLING SPACES IN ACCORDANCE WITH (JP4W-) SECTION 300-22 (C) & (D) OF THE NATIONAL ELECTRIC CODE." ULC logo and statement: UNLESS OTHERWISE SPECIFIED. UNLESS OTHERWISE SPECIFIED. "IN ACCORDANCE WITH CAN/ULC S-102.2 IN SINGLE UNITS OR PAIRS, 4 ft (1220mm) MIN. SPACING, FSR:0, SDC:20." DIMENSIONAL TOLERANCES ARE: ALL DIMENSIONS ARE GIVEN (.X) ±0.05 (1.3) (.XXX) ±0.010 (0.25) IN INCHES, THIRD ANGLE PROJECTION. (.XX) ±0.02 (0.5) ANGLES ± 5°

GB3043DC

ECN - R

lcust

SUP

2/10/06

DATE

JAD

BY

CHK

INITIAL RELEASE

DESCRIPTION

DRAWN BY

CHK 'D

2/10/06

MAT'L:

SEE NOTE 2

NONE

GB3043DC

DWG

SIZE

DRAWING NO.