THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

B

| PANDUIT PART NUMBER | WEIGHT |
|---|---|
| FEIAB58 | 1.10 LB/EACH (499g/EACH) |

G




F




A




A

E NOTES:

1. SEE CURRENT CATALOG FOR ADDITIONAL PART SUFFIXES TO INDICATE PACKAGE QUANTITY.
2. THE FIBER ROUTING EIA/TIA THREADED ROD MOUNTING BRACKET - 5/8" THREADED ROD IS USED TO SUPPORT FIBER-DUCT AND FIBERRUNNER MOUNTING BRACKETS DIRECTLY FROM THE TOP OF A STANDARD 19" (482.6) EIA/TIA RACK WITH THE USE OF 5/8" THREADED ROD (NOT INCLUDED).
3. THE FIBER ROUTING EIA/TIA THREADED ROD MOUNTING BRACKET INCLUDES:
   TWO (2) BRACKET CLIPS,
   TWO (2) 5/8" HELICAL SPRING LOCKWASHERS,
   TWO (2) 5/8-11 HEAVY HEX NUTS.
4. FINISH COLOR: BLACK (EXCEPT FOR HARDWARE)
5. DIMENSIONS IN PARENTHESES ARE IN METRIC.



ENG. REF.: D38558BC_DC_FEIAB58_01.prt

CAD FILENAME/LAYERS

C FEIAB58.pdf

| REV | DATE | BY | CHK | DESCRIPTION | ECN - R | CUST | SUP | GMBH |
|---|---|---|---|---|---|---|---|---|
| - | -------- | --- | -- | G. REVISED PART WEIGHT.<br>F. REVISED PART GEOMETRY. | -------- | -- | -- | |
| - | -------- | --- | -- | E. REVISED GENERAL NOTES.<br>D. REVISED DRAWING TITLE. | -------- | -- | -- | |
| 2 | 7-31-06 | DTP | SMF | C. REVISED CAD FILENAME.<br>B. REV'D DWG. TO CUR. STAND. | 38558-03 | RN | RN | |
| 1 | 12-19-02 | JHNU | RPA | A. REVISED VIEWS. | 38558-03 | RN | RN | |
| R | 11-19-02 | JHNU | RPA | RELEASED TO PRODUCTION | 38558-03 | RN | RN | |

PANDUIT CORP TINLEY PARK, ILLINOIS

FIBER ROUTING EIA/TIA THREADED ROD MOUNTING BRACKET - 5/8" THREADED ROD (FEIAB58)

D CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:
(.X) ± (.XXX) ±
(.XX) ±.03 (.8) ANGLES ±

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY: JHNU
DATE: 11-19-02
CHK'D: RPA
MAT'L: STEEL
SCALE: NONE
DRAWING NO.: 38558-03
DWG: A
SIZE