

Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
Wire Size	4 STR/FLEX (ALL), 3 & 5 FLEX*
Wire Type	Stranded Copper: Class B & C, Compact, Class G, H, I, K, M, Locomotive (*Locomotive only)
Wire Strip Length	5/8 in.
Stud Size	1/4 in.
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90° C
C.S.A Certified Wire Connector	Yes
Panduit Color Code on Barrel	GRAY
Panduit Die Index No. on Barrel	P29
Alternate Industry Die Index No. () on Barrel	(8)



Technical drawing of a Panduit 4 STR/FLEX LCAX4-14 fiber optic cable. The drawing shows the cable with various markings and dimensions. The main body is labeled "PANDUIT" and "4 STR/FLEX LCAX4-14". The connector end is labeled "GRAY DIE P29 (g)". Dimensions include a length of 1.35±.06, a diameter of .27±.02 DIA, and a width of .55±.04. A .37 R Ref dimension is also shown. A note indicates "Color coded barrel markings".



SCALE N/A	DRAWING NO / CAD FILE LCAX4-14-CUST
---------------------	---