



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

MTP TO MTP FIBER OPTIC PATCH CORD								
PANDUIT PART NO.	CABLE				MTP CONNECTOR			
	RATING	FIBER TYPE	COUNT	COLOR	MAX. IL	MIN. RL	BOOT COLOR	
F64D5-5M*Y	PLENUM (OFNP)	62.5/125um	4	ORANGE	0.50dB	20dB	BLACK	
F66D5-5M*Y			6					
F68D5-5M*Y			8					
F612D5-5M*Y			12					
F512D5-5M*Y		50/125um	12	ORANGE	0.50dB	20dB		
FX12D5-5M*Y		10GbE OM3	12	AQUA	0.50dB	26dB		
FX012D5-5M*Y		OPTIMIZED 10GbE OM3			0.35dB	26dB		
FZ12D5-5M*Y		10GbE OM4	12	AQUA	0.50dB	26dB		
FZ12D5-5F*		OPTIMIZED 10GbE OM4			0.35dB	26dB		
FZ012D5-5M*		9/125um OS1	4	YELLOW	0.75dB	55dB		BLACK
FZ012D5-5F*								
F94D5-5M*Y								
F96D5-5M*Y								
F98D5-5M*Y								
F912D5-5M*Y	12							



* - DENOTES PATCH CORD LENGTH, WHERE M = METERS AND F = FEET

										FIBER OPTIC PATCH CORD MTP TO MTP CONFIGURATION CUSTOMER DRAWING					
										 PANDUIT ™ CORP. TINLEY PARK, ILL 60477					
										 THIRD ANGLE PROJECTION		<small>ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED.</small> <small>DIMENSIONAL TOLERANCES ARE:</small> (.X) ±.03 (.XXX) ±.010 (0.3)		<small>DRAWING FILENAME</small> M02779BG_DC/01A	
										<small>DRAWN BY</small> MC		<small>REVIEW DRAWING NUMBERS</small>		<small>PART NO.</small> SEE SHEETS 2 & 3	
										<small>DATE</small> 05-03-07		<small>SCALE</small> NONE		<small>DRAWING NO.</small> 02779-15	
01	09-09-09	EFK		RELEASED TO PRODUCTION	02779-15						<small>CHK'D</small> RAF		<small>SIZE</small> A		
REV	DATE	BY	CHK	DESCRIPTION	ECN	R	CUST	SUP	OTH			<small>SHEET 2 OF 3</small>			

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

MTP TO MTP FIBER OPTIC PATCH CORD							
PANDUIT PART NO.	CABLE				MTP CONNECTOR		
	RATING	FIBER TYPE	COUNT	COLOR	MAX. IL	MIN. RL	BOOT COLOR
F6L12D5-5M*Y	LOW SMOKE ZERO HALOGEN (LSZH) IEC	62.5/125um	12	ORANGE	0.50dB	20dB	BLACK
F5L12D5-5M*Y		50/125um					
FXL12D5-5M*Y		10GbE OM3		AQUA	0.50dB	26dB	
FXOL12D5-5M*		OPTIMIZED 10GbE OM3			0.35dB	26dB	
FZL12D5-5M*		10GbE OM4		AQUA	0.50dB	26dB	
FZL12D5-5F*		OPTIMIZED 10GbE OM4			0.35dB	26dB	
FZOL12D5-5M*							
FZOL12D5-5F*							
F9L12D5-5M*Y				9/125um OS1		YELLOW	0.75dB

* - DENOTES PATCH CORD LENGTH, WHERE M = METERS AND F = FEET

										FIBER OPTIC PATCH CORD MTP TO MTP CONFIGURATION CUSTOMER DRAWING					
										 PANDUIT ™ CORP. TINLEY PARK, ILL 60477					
										 THIRD ANGLE PROJECTION		ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: (.X) ±.03 (.XXX) ±.010 (.3) ±.015 (.XX) ±.03 (.8) ANGLES		DRAWING FILENAME M02779BG_DC/01A SCALE NONE	
										DRAWN BY MC		REVIEW DRAWING NUMBERS		PART NO. SEE SHEETS 2 & 3	
01	09-09-09	EFK	RELEASED TO PRODUCTION			02779-15					DATE 05-03-07		DRAWING NO. 02779-15 SHEET 3 OF 3		SIZE A
REV	DATE	BY	CHK	DESCRIPTION			ECN	R	CUST	SUP	OTH	CHK'D		RAF	