

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. LENGTH PANDUIT (TIP TO TIP) PART NUMBER **FVFLPCY** 1 METER [ 3.28 FEET ] NOTES: 1. SEE CURRENT CATALOG FOR ADDITIONAL PART NUMBER SUFFIXES TO INDICATE PACKAGE QUANTITY. 2. CONSTRUCTED WITH 50/125 MICRON MULTIMODE CABLE AND A PHOSPHOROUS BRONZE SPLIT SLEEVE. 3. EXTRA SPLIT SLEEVES ARE PROVIDED AS REPLACEMENTS. 4. ALL MATERIALS AND COMPONENTS USED MEET THE MATERIAL RESTRICTIONS OF ROHS, (EUROPEAN DIRECTIVE 2002/95/EC ON THE RESTRICTIONS OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE ROHS TECHNICAL ADAPTATION COMMITTEE. **TETHERED** DUSTCAP - TETHERED DUSTCAP BLACK BOOT INTERFACE FOR CONNECTION TO UNTERMINATED OPTI-CRIMP CONNECTOR RED BOOT MULTIMODE ST CONNECTOR FOR CONNECTION TO V.F.L. UNIT V.F.L. PATCHCORD CUSTOMER DRAWING TINLEY PARK, ILL 60477 ALL DIMENSIONS ARE GIVEN IN INCHES, UNLESS OTHERWISE SPECIFIED. DRAWING FILENAME M01686AF\_DC-Y\_02B.prt DIMENSIONAL TOLERANCES ARE: (.XXX) ±.010 (0.3) NONE (.XX) ±.03 [0.8] ANGLES MATERIAL: PART NO. **FVFLPCY** EFK DRAWING NO. DATE SIZE AS NOTED MC 01-18-07 RELEASED TO PRODUCTION 01686-09 06-18-03 01686-09 CHK 'D DATE BY CHK DESCRIPTION ECN - R CUST | SUP ОТН MMW