

Part #							Description	CCD	Mon TVL	Clr TVL	Color		Mono	Temp	VAC	Pwr
					Polycarbonate		 Legend—Day/Nite 36X									
Bronze	Clear	Smoke	Chrome	Gold	Clear	Smoke										
n=2	n=3	n=4	n=6	n=7	n=8	n=9										
GEA-Cn-D36N							36X Day/Night, NTSC, Wall Mount, Coax/UTP	1/4"	530	530	1.40	0.10	0.01	32 to 122F	24	16W
GEA-CEn-D36N							36X Day/Night, NTSC, Wall Mount, Heater and Fan, Coax/UTP	1/4"	530	530	1.40	0.10	0.01	-40 to 122F	24	36W
GEA-Dn-D36N							36X Day/Night, NTSC, Heavy Duty, Coax/UTP	1/4"	530	530	1.40	0.10	0.01	32 to 122F	24	16W
GEA-DEn-D36N							36X Day/Night, NTSC, Heavy Duty, Heater and Fan, Coax/UTP	1/4"	530	530	1.40	0.10	0.01	-13 to 122F	24	66W
GEA-Fn-D36N							36X Day/Night, NTSC, Flush Mount, Coax/UTP, T-Bar Support Kit	1/4"	530	530	1.40	0.10	0.01	32 to 122F	24	16W
GEA-FPn-D36N							36X Day/Night, NTSC, Ultem Flush Mount, Coax/UTP, T-Bar Support Kit	1/4"	530	530	1.40	0.10	0.01	32 to 122F	24	16W
GEA-Hn-D36N							36X Day/Night, NTSC, Pendant Mount, Coax/UTP	1/4"	530	530	1.40	0.10	0.01	32 to 122F	24	16W
GEA-HEn-D36N							36X Day/Night, NTSC, Pendant Mount, Heater and Fan, Coax/UTP	1/4"	530	530	1.40	0.10	0.01	-40 to 122F	24	36W
GEA-PEn-D36N							36X Day/Night, NTSC, PressureDome, Coax/UTP	1/4"	530	530	1.40	0.10	0.01	-40 to 113F	24	66W
GEA-Pn-D36N							36X Day/Night, NTSC, Wall Mount, PressureDome, Coax/UTP	1/4"	530	530	1.40	0.10	0.01	-40 to 113F	24	66W
GEA-Rn-D36N							36X Day/Night, NTSC, Rugged, Coax/UTP	1/4"	530	530	1.40	0.10	0.01	32 to 122F	24	16W
GEA-REn-D36N							36X Day/Night, NTSC, Rugged, Heater and Fan, Coax/UTP	1/4"	530	530	1.40	0.10	0.01	-40 to 122F	24	66W

Choose bubble type and insert corresponding number in place of "n" in part number.

Part #							Description	CCD	Mon TVL	Clr TVL	Color		Mono	Temp	VAC	Pwr	
											lux @1/60s	lux @1/4s	lux @1/4s				
Acrylic						 Legend—Day/Nite 26X											
Bronze	Clear	Smoke	Chrome	Gold	Clear												Smoke
n=2	n=3	n=4	n=6	n=7	n=8												n=9
GEA-Cn-D26N							26X Day/Night, NTSC, Wall Mount, Coax/UTP	1/4"	470	470	1.00	0.07	0.01	32 to 122F	24	16W	
GEA-CEn-D26N							26X Day/Night, NTSC, Wall Mount, Heater and Fan, Coax/UTP	1/4"	470	470	1.00	0.07	0.01	-40 to 122F	24	36W	
GEA-Dn-D26N							26X Day/Night, NTSC, Heavy Duty, Coax/UTP	1/4"	470	470	1.00	0.07	0.01	32 to 122F	24	16W	
GEA-DEn-D26N							26X Day/Night, NTSC, Heavy Duty, Heater and Fan, Coax/UTP	1/4"	470	470	1.00	0.07	0.01	-13 to 122F	24	66W	
GEA-Fn-D26N							26X Day/Night, NTSC, Flush Mount, Coax/UTP, T-Bar Support Kit	1/4"	470	470	1.00	0.07	0.01	32 to 122F	24	16W	
GEA-FPn-D26N							26X Day/Night, NTSC, Ultem Flush Mount, Coax/UTP, T-Bar Support Kit	1/4"	470	470	1.00	0.07	0.01	32 to 122F	24	16W	
GEA-Hn-D26N							26X Day/Night, NTSC, Pendant Mount, Coax/UTP	1/4"	470	470	1.00	0.07	0.01	32 to 122F	24	16W	
GEA-HEn-D26N							26X Day/Night, NTSC, Pendant Mount, Heater and Fan, Coax/UTP	1/4"	470	470	1.00	0.07	0.01	-40 to 122F	24	36W	
GEA-PEn-D26N							26X Day/Night, NTSC, PressureDome, Coax/UTP	1/4"	470	470	1.00	0.07	0.01	-40 to 113F	24	66W	
GEA-Pn-D26N							26X Day/Night, NTSC, Wall Mount, PressureDome, Coax/UTP	1/4"	470	470	1.00	0.07	0.01	-40 to 113F	24	66W	
GEA-Rn-D26N							26X Day/Night, NTSC, Rugged, Coax/UTP	1/4"	470	470	1.00	0.07	0.01	32 to 122F	24	16W	
GEA-REn-D26N							26X Day/Night, NTSC, Rugged, Heater and Fan, Coax/UTP	1/4"	470	470	1.00	0.07	0.01	-40 to 122F	24	66W	

Choose bubble type and insert corresponding number in place of "n" in part number.



Part #								Description	CCD	Mon TVL	Clr TVL	Color		Mono	Temp	VAC	Pwr
								 Legend—Day/Nite 26X w/ Image Stabilization									
Acrylic																	
Bronze	Clear	Smoke	Chrome	Gold	Clear	Smoke											
n=2	n=3	n=4	n=6	n=7	n=8	n=9											
GEA-Cn-D26SN								26X Day/Night w/Image Stabilizer, NTSC, Wall Mount, Coax/UTP	1/4"	470	470	2.00	0.14	0.05	32 to 122F	24	16W
GEA-CEn-D26SN								26X Day/Night w/Image Stabilizer, NTSC, Wall Mount, Heater and Fan, Coax/UTP	1/4"	470	470	2.00	0.14	0.05	-40 to 122F	24	36W
GEA-Dn-D26SN								26X Day/Night w/Image Stabilizer, NTSC, Heavy Duty, Coax/UTP	1/4"	470	470	2.00	0.14	0.05	32 to 122F	24	16W
GEA-DEn-D26N								26X Day/Night w/Image Stabilizer, NTSC, Heavy Duty, Heater and Fan, Coax/UTP	1/4"	470	470	2.00	0.14	0.05	-13 to 122F	24	66W
GEA-Fn-D26SN								26X Day/Night w/Image Stabilizer, NTSC, Flush Mount, Coax/UTP, T-Bar Support Kit	1/4"	470	470	2.00	0.14	0.05	32 to 122F	24	16W
GEA-FPn-D26SN								26X Day/Night w/Image Stabilizer, NTSC, Ultem Flush Mount, Coax/UTP, T-Bar Support Kit	1/4"	470	470	2.00	0.14	0.05	32 to 122F	24	16W
GEA-Hn-D26SN								26X Day/Night w/Image Stabilizer, NTSC, Pendant Mount, Coax/UTP	1/4"	470	470	2.00	0.14	0.05	32 to 122F	24	16W
GEA-HEn-D26SN								26X Day/Night w/Image Stabilizer, NTSC, Pendant Mount, Heater and Fan, Coax/UTP	1/4"	470	470	2.00	0.14	0.05	-40 to 122F	24	36W
GEA-PEn-D26SN								26X Day/Night w/Image Stabilizer, NTSC, PressureDome, Coax/UTP	1/4"	470	470	2.00	0.14	0.05	-40 to 113F	24	66W
GEA-Pn-D26SN								26X Day/Night w/Image Stabilizer, NTSC, Wall Mount, PressureDome, Coax/UTP	1/4"	470	470	2.00	0.14	0.05	-40 to 113F	24	66W
GEA-Rn-D26SN								26X Day/Night w/Image Stabilizer, NTSC, Rugged, Coax/UTP	1/4"	470	470	2.00	0.14	0.05	32 to 122F	24	16W
GEA-REn-D26SN								26X Day/Night w/Image Stabilizer, NTSC, Rugged, Heater and Fan, Coax/UTP	1/4"	470	470	2.00	0.14	0.05	-40 to 122F	24	66W

Choose bubble type and insert corresponding number in place of "n" in part number.

Part #								Description	CCD	Mon TVL	Clr TVL	Color		Mono	Temp	VAC	Pwr
												lux @1/60s	lux @1/4s	lux @1/4s			
Acrylic						Polycarbonate		 CyberDome II—Day/Nite 36X									
Bronze	Clear	Smoke	Chrome	Gold	Clear	Smoke											
n=2	n=3	n=4	n=6	n=7	n=8	n=9											
CYB-Cn-D36N								36x Day/Night, NTSC, Wall Mount, Coax/UTP/Alarm	1/4"	530	530	1.40	0.10	0.01	32 to 122F	24	20W
CYB-CEn-D36N								36x Day/Night, NTSC, Wall Mount, Heater and Fan, Coax/UTP/Alarm	1/4"	530	530	1.40	0.10	0.01	-40 to 122F	24	45W
CYB-Dn-D36N								36x Day/Night, NTSC, Heavy Duty, Coax/UTP/Alarm	1/4"	530	530	1.40	0.10	0.01	32 to 122F	24	20W
CYB-DEn-D36N								36x Day/Night, NTSC, Heavy Duty, Heater and Fan, Coax/UTP/Alarm	1/4"	530	530	1.40	0.10	0.01	-13 to 122F	24	66W
CYB-Fn-D36N								36x Day/Night, NTSC, Flush Mount, Coax/UTP/Alarm, T-Bar Support Kit	1/4"	530	530	1.40	0.10	0.01	32 to 122F	24	20W
CYB-FPn-D36N								36x Day/Night, NTSC, Plenum Rated Flush Mount, Coax/UTP/Alarm, T-Bar Support Kit	1/4"	530	530	1.40	0.10	0.01	32 to 122F	24	20W
CYB-Hn-D36N								36x Day/Night, NTSC, Pendant Mount, Coax/UTP/Alarm	1/4"	530	530	1.40	0.10	0.01	32 to 122F	24	20W
CYB-HEn-D36N								36x Day/Night, NTSC, Pendant Mount, Heater and Fan, Coax/UTP/Alarm	1/4"	530	530	1.40	0.10	0.01	-40 to 122F	24	45W
CYB-PEn-D36N								36x Day/Night, NTSC, PressurDome, Coax/UTP/Alarm	1/4"	530	530	1.40	0.10	0.01	-40 to 122F	24	66W
CYB-Pn-D36N								36x Day/Night, NTSC, Wall Mount, PressurDome, Coax/UTP/Alarm	1/4"	530	530	1.40	0.10	0.01	-40 to 122F	24	66W
CYB-Rn-D36N								36x Day/Night, NTSC, Rugged, Coax/UTP/Alarm	1/4"	530	530	1.40	0.10	0.01	32 to 122F	24	20W
CYB-REn-D36N								36x Day/Night, NTSC, Rugged, Heater and Fan, Coax/UTP/Alarm	1/4"	530	530	1.40	0.10	0.01	-40 to 122F	24	66W

Choose bubble type and insert corresponding number in place of "n" in part number.

Part #							Description	CCD	Mon TVL	Clr TVL	Color		Mono	Temp	VAC	Pwr	
												lux @1/60s	lux @1/4s	lux @1/4s			
Acrylic							 CyberDome II–Day/Nite 26X										
Bronze	Clear	Smoke	Chrome	Gold	Clear	Smoke											
n=2	n=3	n=4	n=6	n=7	n=8	n=9											
CYB-Cn-D26N								26x Day/Night, NTSC, Wall Mount, Coax/UTP/Alarm	1/4"	470	470	1.00	0.07	0.01	32 to 122F	24	20W
CYB-CEn-D26N								26x Day/Night, NTSC, Wall Mount, Heater and Fan, Coax/UTP/Alarm	1/4"	470	470	1.00	0.07	0.01	-40 to 122F	24	45W
CYB-Dn-D26N								26x Day/Night, NTSC, Heavy Duty, Coax/UTP/Alarm	1/4"	470	470	1.00	0.07	0.01	32 to 122F	24	20W
CYB-DEn-D26N								26x Day/Night, NTSC, Heavy Duty, Heater and Fan, Coax/UTP/Alarm	1/4"	470	470	1.00	0.07	0.01	-13 to 122F	24	66W
CYB-Fn-D26N								26x Day/Night, NTSC, Flush Mount, Coax/UTP/Alarm, T-Bar Support Kit	1/4"	470	470	1.00	0.07	0.01	32 to 122F	24	20W
CYB-FPn-D26N								26x Day/Night, NTSC, Plenum Rated Flush Mount, Coax/UTP/Alarm, T-Bar Support Kit	1/4"	470	470	1.00	0.07	0.01	32 to 122F	24	20W
CYB-Hn-D26N								26x Day/Night, NTSC, Pendant Mount, Coax/UTP/Alarm	1/4"	470	470	1.00	0.07	0.01	32 to 122F	24	20W
CYB-HEn-D26N								26x Day/Night, NTSC, Pendant Mount, Heater and Fan, Coax/UTP/Alarm	1/4"	470	470	1.00	0.07	0.01	-40 to 122F	24	45W
CYB-PEn-D26N								26x Day/Night, NTSC, PressurDome, Coax/UTP/Alarm	1/4"	470	470	1.00	0.07	0.01	-40 to 122F	24	66W
CYB-Pn-D26N								26x Day/Night, NTSC, Wall Mount, PressurDome, Coax/UTP/Alarm	1/4"	470	470	1.00	0.07	0.01	-40 to 122F	24	66W
CYB-Rn-D26N								26x Day/Night, NTSC, Rugged, Coax/UTP/Alarm	1/4"	470	470	1.00	0.07	0.01	32 to 122F	24	20W
CYB-REn-D26N							26x Day/Night, NTSC, Rugged, Heater and Fan, Coax/UTP/Alarm	1/4"	470	470	1.00	0.07	0.01	-40 to 122F	24	66W	

Choose bubble type and insert corresponding number in place of "n" in part number.

Part #							Description	CCD	Mon TVL	Clr TVL	Color		Mono	Temp	VAC	Pwr
							 CyberDome II–Day/Nite 23X WDR									
Polycarbonate																
Acrylic																
Bronze	Clear	Smoke	Chrome	Gold	Clear	Smoke										
n=2	n=3	n=4	n=6	n=7	n=8	n=9										
CYB-Cn-D23N							23X Day/Night WDR, Wall Mount Housing, NTSC, Coax/UTP/Alarm	1/4"	470	470	3.00	0.20	0.02	32 to 122F	24	20W
CYB-CEn-D23N							23X Day/Night WDR, Wall Mount Housing, Htr/Fan, NTSC, Coax/UTP/Alarm	1/4"	470	470	3.00	0.20	0.02	-40 to 122F	24	45W
CYB-Dn-D23N							23X Day/Night WDR, Heavy Duty Housing, NTSC, Coax/UTP/Alarm	1/4"	470	470	3.00	0.20	0.02	32 to 122F	24	20W
CYB-DEn-D23N							23X Day/Night WDR, Heavy Duty Housing, Htr/Fan, NTSC, Coax/UTP/Alarm	1/4"	470	470	3.00	0.20	0.02	-13 to 122F	24	66W
CYB-Fn-D23N							23X Day/Night WDR, Flush Mount Housing, NTSC, Coax/UTP/Alarm	1/4"	470	470	3.00	0.20	0.02	32 to 122F	24	20W
CYB-FPn-D23N							23X Day/Night WDR, Plenum Rated Flush Mount Housing, NTSC, Coax/UTP/Alarm	1/4"	470	470	3.00	0.20	0.02	32 to 122F	24	20W
CYB-Hn-D23N							23X Day/Night WDR, Pendant Mount Housing, NTSC, Coax/UTP/Alarm	1/4"	470	470	3.00	0.20	0.02	32 to 122F	24	20W
CYB-HEn-D23N							23X Day/Night WDR, Pendant Mount Housing, Htr/Fan, NTSC, Coax/UTP/Alarm	1/4"	470	470	3.00	0.20	0.02	-40 to 122F	24	45W
CYB-PEn-D23N							23x Day/Night, NTSC, PressurDome, Coax/UTP/Alarm	1/4"	470	470	3.00	0.20	0.02	-40 to 122F	24	66W
CYB-Pn-D23N							23x Day/Night, NTSC, Wall Mount, PressurDome, Coax/UTP/Alarm	1/4"	470	470	3.00	0.20	0.02	-40 to 122F	24	66W
CYB-Rn-D23N							23X Day/Night WDR, Rugged Housing, NTSC, Coax/UTP/Alarm	1/4"	470	470	3.00	0.20	0.02	32 to 122F	24	20W
CYB-REn-D23N							23X Day/Night WDR, Rugged Housing, Htr/Fan, NTSC, Coax/UTP/Alarm	1/4"	470	470	3.00	0.20	0.02	-40 to 122F	24	66W

Choose bubble type and insert corresponding number in place of "n" in part number.

Part #							Description	CCD	Mon TVL	Clr TVL	Color		Mono	Temp	VAC	Pwr									
							 CyberDome II–Day/Nite 18X																		
Acrylic																									
Bronze n=2	Clear n=3	Smoke n=4	Chrome n=6	Gold n=7	Clear n=8	Smoke n=9																			
Polycarbonate																									
CYB-Cn-D18N							18x Day/Night, NTSC, Wall Mount, Coax/UTP/Alarm	1/4"	470	470	0.70	0.05	0.01	32 to 122F	24	20W									
CYB-CEn-D18N							18x Day/Night, NTSC, Wall Mount, Heater and Fan, Coax/UTP/Alarm	1/4"	470	470	0.70	0.05	0.01	-40 to 122F	24	45W									
CYB-Dn-D18N							18x Day/Night, NTSC, Heavy Duty, Coax/UTP/Alarm	1/4"	470	470	0.70	0.05	0.01	32 to 122F	24	20W									
CYB-DEn-D18N							18x Day/Night, NTSC, Heavy Duty, Heater and Fan, Coax/UTP/Alarm	1/4"	470	470	0.70	0.05	0.01	-13 to 122F	24	66W									
CYB-Fn-D18N							18x Day/Night, NTSC, Flush Mount, Coax/UTP/Alarm, T-Bar Support Kit	1/4"	470	470	0.70	0.05	0.01	32 to 122F	24	20W									
CYB-FPn-D18N							18x Day/Night, NTSC, Plenum Rated Flush Mount, Coax/UTP/Alarm, T-Bar Support Kit	1/4"	470	470	0.70	0.05	0.01	32 to 122F	24	20W									
CYB-Hn-D18N							18x Day/Night, NTSC, Pendant Mount, Coax/UTP/Alarm	1/4"	470	470	0.70	0.05	0.01	32 to 122F	24	20W									
CYB-HEn-D18N							18x Day/Night, NTSC, Pendant Mount, Heater and Fan, Coax/UTP/Alarm	1/4"	470	470	0.70	0.05	0.01	-40 to 122F	24	45W									
CYB-PEn-D18N							18x Day/Night, NTSC, PressurDome, Coax/UTP/Alarm	1/4"	470	470	0.70	0.05	0.01	-40 to 122F	24	66W									
CYB-Pn-D18N							18x Day/Night, NTSC, Wall Mount, PressurDome, Coax/UTP/Alarm	1/4"	470	470	0.70	0.05	0.01	-40 to 122F	24	66W									
CYB-Rn-D18N							18x Day/Night, NTSC, Rugged, Coax/UTP/Alarm	1/4"	470	470	0.70	0.05	0.01	32 to 122F	24	20W									
CYB-REn-D18N							18x Day/Night, NTSC, Rugged, Heater and Fan, Coax/UTP/Alarm	1/4"	470	470	0.70	0.05	0.01	-40 to 122F	24	66W									

Choose bubble type and insert corresponding number in place of "n" in part number.

Part #							Description	CCD	Mon TVL	Clr TVL	Color		Mono	Temp	VAC	Pwr
						Polycarbonate	 CyberDome II–Color 22X									
Acrylic																
Bronze n=2	Clear n=3	Smoke n=4	Chrome n=6	Gold n=7	Clear n=8	Smoke n=9										
CYB-Cn-C22N							22x Color, Wall-Mount, NTSC, Coax/UTP/Alarm	1/4"	—	470	3.00	—	n/a	32 to 122F	24	20W
CYB-CEn-C22N							22x Color, Wall-Mount, Htr/Fan, NTSC, Coax/UTP/Alarm	1/4"	—	470	3.00	—	n/a	-40 to 122F	24	45W
CYB-Dn-C22N							22x Color, Heavy Duty Housing, NTSC, Coax/UTP/Alarm	1/4"	—	470	3.00	—	n/a	32 to 122F	24	20W
CYB-DEn-C22N							22x Color, Heavy Duty, Htr/Fan, NTSC, Coax/UTP/Alarm	1/4"	—	470	3.00	—	n/a	-13 to 122F	24	66W
CYB-Fn-C22N							22x Color, Flush Mount Housing, NTSC, Coax/UTP/Alarm	1/4"	—	470	3.00	—	n/a	32 to 122F	24	20W
CYB-FPn-C22N							22x Color, Plenum Rated Flush Mount Housing, Htr/Fan, NTSC, Coax/UTP/Alarm	1/4"	—	470	3.00	—	n/a	32 to 122F	24	20W
CYB-Hn-C22N							22x Color, Pendant Mount Housing, NTSC, Coax/UTP/Alarm	1/4"	—	470	3.00	—	n/a	32 to 122F	24	20W
CYB-HEn-C22N							22x Color, Pendant Mount Housing, Htr/Fan, NTSC, Coax/UTP/Alarm	1/4"	—	470	3.00	—	n/a	-40 to 122F	24	45W
CYB-PEn-C22N							22x Color, NTSC, PressurDome, Coax/UTP/Alarm	1/4"	—	470	3.00	—	n/a	-40 to 122F	24	66W
CYB-Pn-C22N							22x Color, NTSC, Wall Mount, PressurDome, Coax/UTP/Alarm	1/4"	—	470	3.00	—	n/a	-40 to 122F	24	66W
CYB-Rn-C22N							22x Color, Rugged Mount Housing, NTSC, Coax/UTP/Alarm	1/4"	—	470	3.00	—	n/a	32 to 122F	24	20W
CYB-REn-C22N							22x Color, Rugged Mount Housing, Htr/Fan, NTSC, Coax/UTP/Alarm	1/4"	—	470	3.00	—	n/a	-40 to 122F	24	66W

Choose bubble type and insert corresponding number in place of "n" in part number.

Part #								Description					CCD	Mon TVL	Clr TVL	Color		Mono	Temp	VAC	Pwr
																lux @1/60s	lux @1/4s	lux @1/4s			
Acrylic						Polycarbonate			CyberDome II Select—Color 22X												
Bronze	Clear	Smoke	Chrome	Gold	Clear	Smoke															
n=2	n=3	n=4	n=6	n=7	n=8	n=9															
CYS-Cn-C22N								22x Color, Wall-Mount, NTSC, Coax Video Only					1/4"	—	470	3.00	—	n/a	32 to 122F	24	20W
CYS-CEn-C22N								22x Color, Wall-Mount, Htr/Fan, NTSC, Coax Video Only					1/4"	—	470	3.00	—	n/a	-40 to 122F	24	45W
CYS-Dn-C22N								22x Color, Heavy Duty Housing, NTSC, Coax Video Only					1/4"	—	470	3.00	—	n/a	32 to 122F	24	20W
CYS-DEn-C22N								22x Color, Heavy Duty, Htr/Fan, NTSC, Coax Video Only					1/4"	—	470	3.00	—	n/a	-13 to 122F	24	66W
CYS-Fn-C22N								22x Color, Flush Mount Housing, NTSC, Coax Video Only					1/4"	—	470	3.00	—	n/a	32 to 122F	24	20W
CYS-FPn-C22N								22x Color, Plenum Rated Flush Mount Housing, Htr/Fan, NTSC, Coax Video Only					1/4"	—	470	3.00	—	n/a	32 to 122F	24	20W
CYS-Hn-C22N								22x Color, Pendant Mount Housing, NTSC, Coax Video Only					1/4"	—	470	3.00	—	n/a	32 to 122F	24	20W
CYS-HEn-C22N								22x Color, Pendant Mount Housing, Htr/Fan, NTSC, Coax Video Only					1/4"	—	470	3.00	—	n/a	-40 to 122F	24	45W
CYS-Rn-C22N								22x Color, Rugged Mount Housing, NTSC, Coax Video Only					1/4"	—	470	3.00	—	n/a	32 to 122F	24	20W
CYS-REn-C22N								22x Color, Rugged Mount Housing, Htr/Fan, NTSC, Coax Video Only					1/4"	—	470	3.00	—	n/a	-40 to 122F	24	66W

Choose bubble type and insert corresponding number in place of "n" in part number.

Part #	Description	CCD	Mon TVL	Clr TVL	Color		Mono	Temp	VAC	Pwr
					lux @1/60s	lux @1/4s	lux @1/4s			
	 Accord—Integrated Camera Positioning System									
PTZ-HDR1-12N	Pan/Tilt, 12X Zoom, HDR1-DN Day/Night Camera, NTSC Video	1/3"	500	500	0.50	n/a	n/a	-30 to 122F	24	100W
PTZ-HDR1-21N	Pan/Tilt, 21X Zoom, HDR1-DN Day/Night Camera, NTSC Video	1/3"	500	500	0.50	n/a	n/a	-30 to 122F	24	100W
PTZ-IC-18XDN	Pan/Tilt, 18x Auto Focus Day/Night Camera, NTSC Video	1/4"	470	470	0.70	0.1	0.01	-30 to 122F	24	100W
PTZ-IC-26XDN	Pan/Tilt, 26x Auto Focus Day/Night Camera, NTSC Video	1/4"	470	470	1.00	0.07	0.01	-30 to 122F	24	100W
PTZ-NC	Pan/Tilt, No Camera	n/a	n/a	n/a	n/a	n/a	n/a	-30 to 122F	24	100W

