
# 2-Button Keychain Touchpad

Interactive Technologies, Inc.



ITI Part #: 60-607-319.5

#### Overview

The 2-Button Keychain Touchpad is a pocket-size, wireless device that allows the system user to conveniently perform the basic functions of the following ITI Learn Mode security systems:

- Commander 2000<sup>TM</sup> software version 4.0 (60-437-10-95-8Z or 60-437-95-10-17Z)
- Commander 3000 (60-672-95-8Z or 60-672-95-17Z)
- Security Pro 2000 software version 4.0 (60-437-95-8Z-SEC or 60-437-95-17Z-SEC)
- Security Pro 3000 (60-672-95-8Z-SEC or 60-672-95-17Z-SEC)
- Care Taker<sup>®</sup> Plus software version 3.0 (60-435-10-95)
- Security Pro 4000 software version 3.0 (60-435-10-95-SEC)

The touchpad has three functions:

- Arming the system
- Disarming the system
- Sending a panic alarm

The sensor has a wireless transmitter that communicates with any ITI Learn Mode control panel. Patented ITI Learn Mode technology makes it easy to set up the system. Simply by pressing two buttons at the same time and holding them down for two seconds, the touchpad is added into the system. After the touchpad is added, it reports a unique ID code to the control panel whenever it is activated.

## **Applications**

#### 2-Button Keychain Touchpads are recommended for:

- Remote arming and disarming.
- Sending a panic alarm.

#### **Features**

#### 2-Button Keychain Touchpad features include:

- Small size.
- Recessed buttons.
- Green transmission indicator light.

# 2-Button Keychain Touchpad

### **Specifications**

Battery 12 VDC, 33 mAh alkaline battery

Battery Type NEDA 1811A

Battery Brand Duracell MN21

**Typical Battery Life** 5–8 years under recommended operating conditions

**Transmitter Frequency** 319.5 MHz (crystal-controlled)

Transmitter Frequency  $\pm 5 \text{ kHz}$ 

**Tolerance** 

**Transmitter Bandwidth** 24 kHz

Modulation Type Amplitude Shift Key (ASK)

Unique ID Codes 16 million

Peak Field Strength  $> 40,000 \mu V/m @ 3m$ 

**Operating Temperature**  $10^{\circ}\text{F} (-12^{\circ}\text{C}) \text{ to } 120^{\circ}\text{F} (49^{\circ}\text{C})$ 

**Enclosure** ABS Plastic

Weight 0.8 oz. (22.68 g)

**Dimensions** 1.375'' (3.5 cm) wide x 2.25'' (5.7 cm) long x 0.375'' (0.95 cm) thick

Color Black

**FCC Standard** CFR Chapter 47, FCC Part 15

#### Installation

#### **System Programming**

The touchpad can be added to the system as a sensor or wireless touchpad. If added as a sensor, the panel identifies the touchpad by its sensor number and reports this number to the central station. Also, the touchpad can be bypassed, which disables all touchpad functions.

If the touchpad is added as a wireless touchpad, the panel identifies the touchpad as user number 20\* or user number  $41^{\dagger}$  and reports this number to the central station. When added as a wireless touchpad, it cannot be bypassed.

Interactive Technologies, Inc. 2266 Second Street North North Saint Paul, MN 55109 1-800-777-1415

Specifications are subject to change without notice.

Fax: 1-612-779-4890

Ordering Information
ITI Part #: 60-607-319.5

ITI Document #: 466-1072 (Rev. A) (Spec Sheets available in quantities of 50)

ITI and CareTaker are registered trademarks of Interactive Technologies, Inc. Commander 2000 is a trademark of Interactive Technologies, Inc.

<sup>\*</sup> Commander 2000/3000 and Security Pro 2000/3000

<sup>&</sup>lt;sup>†</sup> CareTaker Plus and Security Pro 4000