Product Specifications



760105536 | P-072-LN-5K-F12BK/25D

Indoor/Outdoor Single Jacket All-Dielectric Plenum Stranded Loose Tube Gel-Free Cable

Representative Image



General Specifications

Cable Type	Stranded loose tube
Construction Type	Non-armored
Subunit Type	Gel-free

Construction Materials

Fiber Type Solution	LazrSPEED® 550, 50 µm multimode fiber
Total Fiber Quantity	72
Fiber Type	LazrSPEED® 550, 50 µm multimode fiber
Fiber Type, quantity	72
Fibers Per Subunit, quantity	12
Jacket Color	Black
Jacket UV Resistance	UV stabilized

Dimensions

Buffer Tube/Subunit Diameter	2.50 mm | 0.10 in
Cable Weight	105.0 kg/km | 71.0 lb/kft
Diameter Over Jacket	10.10 mm | 0.40 in
Subunit, quantity	6

Physical Specifications

Minimum Bend Radius, loaded	15.2 cm | 6.0 in
Minimum Bend Radius, unloaded	10.1 cm | 4.0 in

©2012 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.
All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: February 19, 2012

Tensile Load, long term, maximum	180 lbf | 800 N
Tensile Load, short term, maximum	2700 N | 607 lbf
Vertical Rise, maximum	778.0 m | 2552.5 ft

Flame Test Specifications

Flame Test Listing	NEC OFNP (ETL) and c(ETL)
Flame Test Method	NFPA 262

Environmental Specifications

Environmental Space	Plenum
Installation Temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Storage Temperature	-40 °C to +75 °C (-40 °F to +167 °F)

Mechanical Test Specifications

Compression	125 lb/in | 22 N/mm
Compression Test Method	FOTP-41 | IEC 60794-1-2, Section 7
Flex	35 cycles
Flex Test Method	FOTP-24 | IEC 60794-1-2, Section 10
Impact	2.17 ft lb | 2.94 N-m
Impact Test Method	FOTP-25 | IEC 60794-1-2, Section 8
Strain	See long and short term tensile loads
Strain Test Method	FOTP-33 | IEC 60794-1-2, Section 5
Twist	10 cycles
Twist Test Method	FOTP-85 | IEC 60794-1-2, Section 11
Water Penentration	24 h
Water Penentration Test Method	FOTP-82 | IEC 60794-1-2, Section 24

Environmental Test Specifications

Cable Freeze	-2 °C | 28 °F
Cable Freeze Test Method	FOTP-98
Heat Age	-40 °C to +85 °C (-40 °F to +185 °F)
Heat Age Test Method	Not applicable
Low High Bend	-30 °C to +60 °C (-22 °F to +140 °F)
Low High Bend Test Method	FOTP-28 | IEC 60794-1-2, Section 28
Temperature Cycle	-40 °C to +70 °C (-40 °F to +158 °F)
Temperature Cycle Test Method	FOTP-3 | IEC 60794-1-2, Section 22

Qualification Specifications

Cable Qualification Standards	ANSI/ICEA S-104-696-2001 | EN 187105 | Telcordia GR-409-CORE Issue 2

Regulatory Compliance/Certifications

Agency	**Classification**
RoHS 2002/95/EC	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

©2012 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.
All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: February 19, 2012

Product Specifications

760105536 | P-072-LN-5K-F12BK/25D

RoHS COMPLIANT

Included Products

CS-5K-LT (Product Component—not orderable) — LazrSPEED® 550 OM4 Multimode Fiber

©2012 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.
All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: February 19, 2012