



## 760026906 | ROC-BKPLN

### ROC Backplane Expanded Beam Connector

- Contact an authorized CommScope distributor for current pricing information.

#### Construction Materials

Fiber Type	100/140 $\mu$ m multimode fiber
Ferrule Geometry	Multifiber

#### Dimensions

Compatible Cable Diameter	0.9 mm   0.0 in
Length	32.0 mm   1.3 in

#### Environmental Specifications

Humidity Test Method	MIL-STD-1344A, Method 1002 Type 1, Test Condition A
Salt Fog Test Method	ANSI/EIA-RS-455-13   MIL-STD-810E, Method 509
Sand and Dust Test Method	MIL-STD-202F, Method 110A
Thermal Shock Test Method	MIL-STD-202F, Method 107, Test Condition B

#### General Specifications

Interface	ROC
Body Style	Backplane
Interface Feature	Expanded beam
Color	Red
Package, quantity	1

#### Mechanical Specifications

Cable Retention Strength, maximum	0.91 kg @ 0 ° 2.00 lb @ 0 °
Handling Shock Test Method	MIL-STD-810E, Method 516, Procedure VI
Mating Durability Test Method	MIL-M-28787D
Mechanical Shock Test Method	ANSI/EIA/TIA-455-32A, Test Condition A   MIL-STD-810E, Method 516, Procedure 1
Tensile Test Method	ANSI/EIA/TIA-455-6B
Vibration Test Method	ANSI/EIA/TIA-455-32A, Test Condition A   MIL-STD-202F, Method 214, Test Condition 1

#### Optical Performance

Insertion Loss, typical	0.70 dB
Return Loss, minimum	20.0 dB
Insertion Loss Change, mating	0.50 dB
Insertion Loss Change, temperature	0.50 dB

#### Optical Specifications

Optical Components Standard	ANSI/EIA-455-171, Method A1
-----------------------------	-----------------------------

## Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

### \* Footnotes

Insertion Loss Change, mating	Maximum insertion loss change after 500 matings
Insertion Loss Change, temperature	Maximum insertion loss change from 0 °C to +60 °C (+32 °F to +140 °F)