Number of contacts

2

Identification	Part number Male insert (M)	Part number Female insert (F)	Drawing	Dimensions in mm
Crimp terminal Order crimp contacts separately			M	
Range of delivery: - 1 module - 2 locking sleeves - 2 heat shrink tubes	**09 14 002 3021**	**09 14 002 3121**	F	
Removal tool for locking sleeve	**09 99 000 0327**	**09 99 000 0327**		

Identification	Wire gauge (mm²)	Part number Male contact	Part number Female contact	Drawing	Dimensions in mm
Crimp contacts				Operating contact Identification	
silver plated	0.5	**09 33 000 6121**	**09 33 000 6220**		
	0.75	**09 33 000 6114**	**09 33 000 6214**		
	1	**09 33 000 6105**	**09 33 000 6205**		
	1.5	**09 33 000 6104**	**09 33 000 6204**		
	2.5	**09 33 000 6102**	**09 33 000 6202**		
	3	09 33 000 6106	09 33 000 6206		
	4	**09 33 000 6107**	**09 33 000 6207**		

Identification	Wire gauge		Stripping length
no groove	0.5 mm²	AWG 20	9.5 mm
1 groove*	0.75 mm²	AWG 18	9.5 mm
1 groove	1 mm²	AWG 18	9.5 mm
2 grooves	1.5 mm²	AWG 16	9.5 mm
3 grooves	2.5 mm²	AWG 14	9.5 mm
wide groove	3 mm²	AWG 12	9.5 mm
no groove	4 mm²	AWG 12	9.5 mm

* on the back crimp collar

Stock items in bold type