

Specification Grade Ground Fault Circuit Interrupters

2-Pole, 3-Wire Grounding
Combo: 15A, 125V/AC Receptacle; 15A, 120V/AC Switch
Dead Front: 20A, 125V/AC

	Device Type	Specification Grade Combination GFCI Receptacle & Switch, 15A: VGFS15, ___-MSP	Specification Grade Blank Face (Dead-Front) GFCI, 20A: VGFD20 Series	
	Wiring Type	Back & side wire	Back & side wire	
	Testing & Code Compliance	<ul style="list-style-type: none"> cULus Listed to UL 498 and UL 943, file no. E60120 Meets all UL 943 (GFCI), UL 498 (Receptacles), UL 20 (Switch) and applicable CSA requirements NOM certified 	<ul style="list-style-type: none"> cULus Listed to UL 498 and UL 943, file no. E60120 Meets all UL 943 (GFCI), UL 498 (Receptacles), UL 508 (Motor Control) and applicable CSA requirements NOM certified 	
Specifications: Environmental		Flammability	Meets UL 94 requirements; V2 rated	Meets UL 94 requirements; V2 rated
		Temperature Rating	-35°C to 66°C (-40°F to 167°F)	-35°C to 66°C (-40°F to 167°F)
Specifications: Electrical	Dielectric Voltage	Withstands 2000V per UL 498	Withstands 2000V per UL 498	
	Current Interrupting	Yes, at full-rated current	Yes, at full-rated current	
	Temperature Rise	Max. 30°C (86°F) after 100 cycles of overload @ 150% of rated current (DC)	N/A	
	Short Circuit Testing	Meets and exceeds 10 ka	Meets and exceeds 10 ka	
Specifications: Mechanical	Terminal Accommodation	#14 - #10 AWG	#14 - #10 AWG	
	Voltage Ratings	Permanently marked on device	Permanently marked on device	
	Horsepower Ratings	Switch rated for motor loads per UL 20: 15A: @ 120V/AC = 1/2 HP, max. amps: 12 full-load amps	Rated for motor loads per UL 508: 20A: @ 125V/AC = 1.5 HP, max. amps 20 full load amps	
Materials:	Top Housing	Thermoplastic, nylon	Thermoplastic, nylon	
	Bottom Housing	PVC	PVC	
	Strap	0.047" thick steel, zinc plated	0.047" thick steel, zinc plated	
	Line Contacts	0.030" thick brass	N/A	
	Terminal & Ground Screws	#8-32 steel, brass plated; neutral screw nickel plated, ground screw green	#8-32 steel, brass plated; neutral screw nickel plated, ground screw green	
	Terminal Clamps	0.070" thick steel	0.070" thick steel	