

Product information STASEI 5 grau/grey

Industrial Connecting Solutions: Rectangular Connectors: Power Connectors (ST series): Panel-mounted connector: STASEI 5 grau/grey http://www.e-catalog.beldensolutions.com/link/57078-24228-256261-24351-24356-36012/en/conf/uistate STASEI 5 grau/grey Name Panel-mounted connector, not assemled with added contacts and added gasket **Delivery informations** Availability available **Product description** Panel-mounted connector, not assemled with added contacts and added gasket Description STASEI 5 grau/grey Туре Order No. 931 697-106 Type of contact male 5 + PE Number of contacts Conductor size max. 1 mm² **Housing Color** grey Contact bearer color black Technical data Pin dimensions 2 mm AC 400 V / DC 250 V Rated voltage Rated current DC 10 A / AC 6 A Contact resistance <= 10 m0hmType of termination screws Mounting Schrauben Material Contact material Cu Zn Contact surface material Ag Contact bearer material PA Housing material PA **Environmental conditions** Protection class (IEC 60529) IP 54 Pollution severity Temperature range -30 °C to +90 °C Inflammability class Housing UL 94 HB UL 94 V-0 Contact bearer **Approvals** VDE VDE SEV SEV Packing unit Packaging unit 100 pieces



Scope of delivery and accessories
Accessories to order separately

safety brackets STASI 3, order no. 732 045-001




 $Industrial\ Connecting\ Solutions: Rectangular\ Connectors: Power\ Connectors\ (ST\ series): Panel-mounted\ connector: STASEI\ 5\ grau/grey$

http://www.e-catalog.beldensolutions.com/link/57078-24228-256261-24351-24356-36012/en/conf/uistate

Picture

Drawing



Belden Deutschland GmbH

Im Gewerbepark 2 58579 Schalksmühle Germany

Phone: +49 7127/14-1806 E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.

