

Product information G 4 A 1 M grau/grey

Industrial Connecting Solutions:Rectangular Connectors:DIN VDE 0627 / IEC 61984 Connectors (G serie):Cable plug:G 4 A 1 M grau/grey

G 4 A 1 M grau/grey

http://www.e-catalog.beldensolutions.com/link/57078-24228-256261-24347-24349-36965/en/conf/uistate

(6)

	Surface mounted connector for printed circuit boards with solder contacts
Delivery informations	
Availability	available
Product description	
Description	Surface mounted connector for printed circuit boards with solder contacts
Туре	G 4 A 1 M grau/grey
Order No.	931 807-106
Type of contact	blade contacts
Number of contacts	4
Standard	DIN VDE 0627 / IEC 61984
Housing Color	grey
Technical data	
Pin dimensions	2.8 mm x 0.8 mm
Rated voltage	AC/DC 50 V
Rated current	10 A
Contact resistance	<= 4 m0hm
Type of termination	solder (solder tabs for printed circuits)
Suitable cables	4 mm to 7.5 mm
Material	
Contact surface material	Sn
Contact bearer material	PA
Housing material	PA
Environmental conditions	
Protection class (IEC 60529)	IP 65
Pollution severity	3
Temperature range	-40 °C to +90 °C
Inflammability class	
Housing	94 HB
Contact bearer	94 HB
Approvals	
VDE	VDE
Packing unit	
Packaging unit	100 pieces
Scope of delivery and accessories	
Scope of delivery	1 surface mounted connector
Accessories to order separately	can be plugged into G 4 W 1 F grau, G 4 KW 1 F 2m





Industrial Connecting Solutions:Rectangular Connectors:DIN VDE 0627 / IEC 61984 Connectors (G serie):Cable plug:G 4 A 1 M grau/grey

http://www.e-catalog.beldensolutions.com/link/57078-24228-256261-24347-24349-36965/en/conf/uistate

Picture

Drawing



Belden Deutschland GmbH

lm Gewerbepark 2 58579 Schalksmühle

Germany

Phone: +49 7127/14-1806 E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.

