



Product information GO 6 FAV M schwarz/black

Industrial Connecting Solutions:Rectangular Connectors:DIN VDE 0627 / IEC 61984 Connectors (G serie):Cable plug:GO 6 FAV M schwarz/black

<http://www.e-catalog.beldensolutions.com/link/57078-24228-256261-24347-24349-36973/en/conf/ui/state>

Name GO 6 FAV M schwarz/black



Surface mounted connector with flange with solder contacts

Delivery informations

Availability available

Product description

Description Surface mounted connector with flange with solder contacts

Type GO 6 FAV M schwarz/black

Order No. 932 669-100

Type of contact blade contacts

Number of contacts 6

Standard DIN VDE 0627 / IEC 61984

Housing Color black

Technical data

Pin dimensions 2.8 mm x 0.8 mm

Rated voltage AC/DC 50 V

Rated current 6 A

Contact resistance $\leq 4 \text{ m}\Omega$

Type of termination solder

Mounting screws

Material

Contact surface material Sn

Contact bearer material PA

Housing material PA

Environmental conditions

Protection class (IEC 60529) IP 65

Pollution severity 3

Temperature range -40 °C to +90 °C

Inflammability class

Housing 94 V-1

Contact bearer 94 V-1

Packing unit

Packaging unit 100 pieces

Scope of delivery and accessories


Scope of delivery 1 surface mounted connector, 1 flat gasket

Accessories to order separately can be plugged into GO 6 WF schwarz/black

Industrial Connecting Solutions:Rectangular Connectors:DIN VDE 0627 / IEC 61984 Connectors (G serie):Cable plug:GO 6 FAV M schwarz/black
<http://www.e-catalog.beldensolutions.com/link/57078-24228-256261-24347-24349-36973/en/conf/ui/state>

Picture

Drawing



Belden Deutschland GmbH

Im Gewerbepark 2
58579 Schalksmühle
Germany
Phone: +49 7127/14-1806
E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.