




Product information ACA11-M12 (EEC)

Industrial Ethernet: System Accessories: Adapter cable: ACA11-M12 (EEC)
<http://www.e-catalog.beldensolutions.com/link/57078-24455-24544-24546-40966/en/conf/ui/state>

Name	ACA11-M12 (EEC)
	

Auto-configuration adapter, with M12 connection, saves two different versions of configuration data and operating software from the connected switch. It enables managed switched to be easily commissioned and quickly replaced.

Delivery informations

Availability	available
--------------	-----------

Product description

Description	Auto-configuration adapter, with M12 connection, saves two different versions of configuration data and operating software from the connected switch. It enables managed switched to be easily commissioned and quickly replaced.
-------------	---

Type	ACA11-M12 (EEC)
------	-----------------

Order No.	943 972-001
-----------	-------------

More Interfaces

To the RS232 interface on the switch	n/a
--------------------------------------	-----

To the RS232 interface on the PC or notebook	n/a
--	-----

To the USB interface on the switch	M12 connection
------------------------------------	----------------

Power requirements

Operating voltage	via the USB interface on the switch
-------------------	-------------------------------------

Service

Diagnostics	writing to ACA, reading from ACA, writing/reading not OK; (display using LEDs on the switch)
-------------	---

Configuration	via USB interface of the switch and via SNMP/Web
---------------	--

Ambient conditions

Operating temperature	-40 °C ... 70 °C
-----------------------	------------------

Storage/transport temperature	-40 °C ... 85 °C
-------------------------------	------------------

Relative humidity (non-condensing)	10 % ... 95 %
------------------------------------	---------------

MTBF	359 years (MIL-HDBK-217F)
------	---------------------------

Mechanical construction

Dimensions (W x H x D)	90 mm x 27 mm x 12 mm
------------------------	-----------------------

Mounting	plug-in module
----------	----------------

Weight	25 g
--------	------

Protection class	IP67
------------------	------

Cable length	50 cm
--------------	-------

Mechanical stability

IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
----------------------	---------------------------------

IEC 60068-2-6 vibration	1 g, 10 Hz - 150 Hz, 30 cycles
-------------------------	--------------------------------

EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
--	--

EN 61000-4-3 electromagnetic field	10 V/m
------------------------------------	--------

EMC emitted immunity

EN 55022	EN 55022
----------	----------

Approvals

Hazardous locations	cUL 1604 Class1 Div 2 (pending)
---------------------	---------------------------------

Shipbuilding	Germanischer Lloyd (pending)
--------------	------------------------------

Safety of industrial control equipment	cUL 508
--	---------

Employment in vehicles	E1
------------------------	----

Scope of delivery and accessories

Scope of delivery	device, operating manual
-------------------	--------------------------

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.