




## Product information BAT54-F Single

Industrial Ethernet:Industrial Wireless LAN:Chassis:BAT-F:BAT54-F Single	
<a href="http://www.e-catalog.beldensolutions.com/link/57078-24455-49859-24497-78529-40968/en/conf/ui/state">http://www.e-catalog.beldensolutions.com/link/57078-24455-49859-24497-78529-40968/en/conf/ui/state</a>	
<b>Name</b>	BAT54-F Single
	
	Dualband Ruggedized Industrial Wireless LAN Access Point/Client with one radio module with IEEE 802.11a/b/g/h/i and two PoE/LAN ports for installation in harsh environment
<b>Delivery informations</b>	
<b>Availability</b>	available
<b>Product description</b>	
<b>Description</b>	Dualband Ruggedized Industrial Wireless LAN Access Point/Client with one radio module with IEEE 802.11a/b/g/h/i and two PoE/LAN ports for installation in harsh environment
<b>Port type and quantity</b>	1 x WLAN interfaces, up to 8 SSIDs per WLAN interface, 2 x LAN port 10/100BASE-TX, autosensing, Power over Ethernet according to IEEE 802.3af
<b>Type</b>	BAT54-F Single
<b>Order No.</b>	943 959-116
<b>Radio technology</b>	
<b>Antenna connector</b>	2 x N-type jack antenna connectors
<b>Range</b>	Depending on type of antenna, frequency range and data rate
<b>Frequency band</b>	1 x radio modules, 2.4 GHz and 5 GHz: 2400-2483,5 MHz (ISM) and 5170-5810 MHz
<b>Modulation</b>	22M0F7D(DSSS/OFDM) @ 2,4 GHz 20M0G7D (OFDM) @ 5 GHz
<b>Radio topology</b>	WLAN access point, bridge, router, point-to-point, client, client-bridge mode, WDS - Wireless Distribution System, fixed mesh with RSTP
<b>Power requirements</b>	
<b>Operating voltage</b>	2 x Power-over-Ethernet according to IEEE802.3af; redundant to each other
<b>Current consumption at 24 V DC</b>	-
<b>Current consumption</b>	PoE (DC 48 V): 167 mA
<b>Ambient conditions</b>	
<b>Operation temperature</b>	-30 °C to +60 °C
<b>Storage/transport temperature</b>	-40 °C to +70 °C
<b>Relative humidity (non-condensing)</b>	max. 95%
<b>MTBF</b>	43.3 years
<b>Mechanical construction</b>	
<b>Dimensions (W x H x D)</b>	261 mm x 189 mm x 55 mm
<b>Mounting</b>	for wall and mast mounting
<b>Protection class</b>	IP 65, IP 67
<b>Approvals</b>	
<b>Safety of information technology equipment</b>	EN 60950
<b>Radio</b>	EN 300328, EN 301893, notified in all countries of EU. For other notifications or certifications please refer to INET-Sales@hirschmann.de
<b>Environmental</b>	EN 61000-6-2, EN 61131 for use in automation environment; E1 certification for use in vehicles; EN50155 for use in trains; Tested for salt spray according to DIN EN 60068-2-52
<b>Scope of delivery and accessories</b>	
<b>Scope of delivery</b>	Device, 2 dipole antennas, CD, M12 connector, 1 x 50 Ohm terminator, mounting material
<b>Accessories to order separately</b>	External antennas for 802.11b/g and 802.11a/h operation adapter cable and surge arrestor, mast mount material

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.