



## Product information MACH102-8TP-F

Industrial Ethernet:Workgroup Switches:Fast-/Gigabit Ethernet Workgroup Switches, 10/24 ports :MACH102-8TP-F

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49848-85612-40980/en/conf/ui/istate>

<b>Name</b>	MACH102-8TP-F
	
	10 port Fast Ethernet/Gigabit Ethernet Industrial Workgroup Switch (2 x GE, 8 x FE), managed, Software Layer 2 Professional, Store-and-Forward-Switching, fanless Design
<b>Delivery informations</b>	
<b>Availability</b>	available
<b>Product description</b>	
<b>Description</b>	10 port Fast Ethernet/Gigabit Ethernet Industrial Workgroup Switch (2 x GE, 8 x FE), managed, Software Layer 2 Professional, Store-and-Forward-Switching, fanless Design
<b>Port type and quantity</b>	10 ports in total; 8x (10/100 BASE-TX, RJ45) and 2 Gigabit Combo ports
<b>Type</b>	MACH102-8TP-F
<b>Order No.</b>	943 969-201
<b>More Interfaces</b>	
<b>Power supply/signaling contact</b>	1 x plug-in terminal block, 2-pin, output manual or automatic switchable (max. 1 A, 24 V DC bzw. 24 V AC)
<b>V.24 interface</b>	1 x RJ11 socket, serial interface for device configuration
<b>USB interface</b>	1 x to connect auto-configuration adapter ACA21-USB
<b>Network size - length of cable</b>	
<b>Twisted pair (TP)</b>	0 - 100m
<b>Multimode fiber (MM) 50/125 µm</b>	Fast Ethernet: cf. SFP LWL module M-FAST SFP-MM/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC
<b>Multimode fiber (MM) 62.5/125 µm</b>	Fast Ethernet: cf. SFP LWL module M-FAST SFP-MM/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC
<b>Single mode fiber (SM) 9/125 µm</b>	Fast Ethernet: cf. SFP LWL module M-FAST SFP-SM/LC and M-FAST SFP-SM+/LC; Gigabit Ethernet: cf. SFP LWL module M-SFP-LX/LC
<b>Single mode fiber (LH) 9/125 µm (long haul transceiver)</b>	Fast Ethernet: cf. SFP LWL modul M-FAST SFP-LH/LC; Gigabit Ethernet: cf. SFP LWL modul M-SFP-LH/LC and M-SFP-LH+/LC
<b>Network size - cascading</b>	
<b>Line - / star topology</b>	any
<b>Ring structure (HIPER-Ring) quantity switches</b>	50 (reconfiguration time < 0,3 sec.)
<b>Power requirements</b>	
<b>Operating voltage</b>	100 - 240 VAC, 47 - 63 Hz
<b>Power output in Btu (IT) h</b>	41
<b>Rated current</b>	0.4 - 0.2 A
<b>Power consumption</b>	12 W
<b>Software</b>	
<b>Management</b>	serial Interface, web interface, SNMP V1/V2, HViSion file transfer SW HTTP/TFTP
<b>Diagnostics</b>	LEDs, log-file, syslog, signal contact, RMON (statistic, history, alarms, events), port mirroring, topology discovery 802.1AB, cable diagnostic
<b>Configuration</b>	Comand line interface (CLI), TELNET, BootP, DHCP, DHCP option 82, HIDiscovery, auto-configuration adapter (ACD11, ACA21-USB), Watchdog configuration; integrated DHCP server
<b>Security</b>	Port security (IP and MAC), SNMP V3, SSH, authentication (802.1x)
<b>Redundancy functions</b>	HIPER-ring (ring structure), MRP (IEC-ring functionality), RSTP 802.1D-2004, redundant network/ring coupling, dual homing, link aggregation
<b>Filter</b>	QoS 4 Klassen, Portpriorisierung (IEEE 802.1D/p), VLAN (IEEE 802.1Q), shared VLAN learning, Multicast (IGMP Snooping/Querier), Multicast Detection unknown Multicast, Broadcastlimiter, Fast Aging, Multicast GMRP IEEE 802.1D
<b>Industrial Profiles</b>	EtherNet/IP, PROFINET, configuration and diagnostic via automation software tools like e.g. STEP7, or Control Logix
<b>Time synchronisation</b>	Sntp server, realtime clock with energy buffer
<b>Flow control</b>	Flow Control 802.3x, Port Priority 802.1D/p, Priority (TOS/DIFFSERV), Prio (MAC/IP), Prio Mapping (TOS Layer2), Traffic Shaping (Unicast, Multicast, Broadcast) Ingress / Egress
<b>Ambient conditions</b>	
<b>Operating temperature</b>	0° - +50°C
<b>Storage/transport temperature</b>	-20° - +85°C



## Industrial Ethernet:Workgroup Switches:Fast-/Gigabit Ethernet Workgroup Switches, 10/24 ports :MACH102-8TP-F

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49848-85612-40980/en/conf/ui/state>

<b>Relative humidity (non-condensing)</b>	10% to 95%
<b>MTBF</b>	15.67 years (MIL-HDBK-217F Gb 25°C)
<b>Mechanical construction</b>	
<b>Dimensions (W x H x D)</b>	448 x 44 x 310 (without fixing bracket)
<b>Mounting</b>	19" control cabinet
<b>Weight</b>	3.60 kg
<b>Protection class</b>	IP20
<b>EMC interference immunity</b>	
<b>EN 61000-4-2 electrostatic discharge (ESD)</b>	4 kV contact discharge, 8 kV air discharge
<b>EN 61000-4-3 electromagnetic field</b>	10 V/m (80 - 2700 MHz)
<b>EN 61000-4-4 fast transients (burst)</b>	2 kV power line, 4 kV data line
<b>EN 61000-4-5 surge voltage</b>	power line: 2 kV (line/earth), 1 kV (line/line), 4 kV data line
<b>EN 61000-4-6 conducted immunity</b>	10 V (150 kHz - 80 MHz)
<b>EMC emitted immunity</b>	
<b>FCC CFR47 Part 15</b>	FCC 47 CFR Part 15 Class A
<b>EN 55022</b>	EN 55022 Class A
<b>Approvals</b>	
<b>Safety of industrial control equipment</b>	cUL 508
<b>Safety of information technology equipment</b>	cUL 60950-1
<b>Scope of delivery and accessories</b>	
<b>Scope of delivery</b>	MACH100 device, terminal block for signal contact, 2 brackets with fasteningscrews (pre-assembled), housing feet - stick-on, non-heating appliance cable - Euro model, CD-ROM with user manual, installation user manual
<b>Accessories to order separately</b>	Fast Ethernet SFP modules, Gigabit Ethernet SFP modules, autoConfiguration Adapter ACA21-USB, terminal cable, Industrial Hivision Network Management software

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.