



HIRSCHMANN

A BELDEN BRAND

Product information MACH4002-48G+3X-L3P

Industrial Ethernet:Backbone Switches:Chassis:MACH4002-48G+3X-L3P

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49838-24526-40297/en/conf/ulistate>

Name		MACH4002-48G+3X-L3P
		
		MACH 4000, modularer, managed Industrial Backbone-Router, Layer 3 Switch mit Software Professional .
Delivery informations		
Availability		available
Product description		
Description		MACH 4000, modularer, managed Industrial Backbone-Router, Layer 3 Switch mit Software Professional .
Port type and quantity		up to 48 Gigabit-ETHERNET and 3x 10Gigabit-ETHERNET ports, thereof up to 16 Gigabit-ETHERNET ports via media modules practicable, 3x 10Gigabit XFP sockets and 16 Gigabit TP (10/100/1000Mbit/s) ports are integral installed
Type		MACH4002-48G+3X-L3P
Order No.		943 878-301
More Interfaces		
Power supply/signaling contact		1 plug-in terminal block, 4-pin, 2x egresses manual or automatic switchable (1 A at max. 60 V DC or max. 30 V)
V.24 interface		1 x RJ11 socket, serial interface to the configuration of devices
USB interface		1USB interface to connect auto-configuration adapter (ACA21-USB)
Network size - cascability		
Line - / star topology		any
Ring structure (HIPER-Ring) quantity switches		ring-recovery time < 50 ms typ. at LWL
Power requirements		
Operating voltage		power supply unit M4-S-xx or M4-Power Chassis with power supply unit please order separately
Power consumption		70 W (without media modules)
Service		
Management		serial interface, web interface, SNMP V1/V2/V3, HiVision, file transfer SW HTTP/TFTP
Diagnostics		LEDs (power, link status, data, 100 Mbit/s, auto-negotiation, full-duplex, error, redundancy management, ring-port, LED-test), signal contact, syslog, logfile, RMON, port mirroring, Topology Discovery IEEE 802.1AB (LLDP)
Configuration		command line interface (CLI), TELNET, BootP, DHCP, DHCP Option 82, HiDiscovery, auto-configuration adapter (ACA21-USB)
Security		port-security (MAC- and IP-adresses), access control to agent (VLAN/IP) authentication 802.1x, SSH, SSL, SNMP V3
Other services		QoS 8 classes, prioritisation (IEEE 802.1D/p), VLAN (IEEE 802.1Q), multicast (IGMP snooping/querier), broadcastlimiter, flow control IEEE 802.3x, SNTP (Simple Network Time Protocol), TOS (Type of Service) Diff.-Serv (DSCP), TOS-Prio-Mapping, protocol based VLANs (IP, nonIP Traffic), Traffic Shaping
Prepared for		MSTP-802.1s
Routing		static routing, VRRP router redundancy; layer 3 - ACL, HiVRRP router redundancy < 500 ms
Dynamic routing		RIP V1/2, OSPF
Multicast routing		Multicast routing DVMRP/PIM DM
Redundancy		
Redundancy functions		HIPER-Ring (ring structure), RSTP IEEE 802.1D/w (rapid spanning tree protocol), redundant network/ring coupling (master/slavefunctionality), redundant 24 V power supply by M4-Power basic device, redundant signal contact, link aggregation dynamic and static (max. 7 trunks, 8 ports/trunk, LACP)
Ambient conditions		
Operating temperature		0 °C to +60 °C
Storage/transport temperature		-25 °C to +70 °C
Relative humidity (non-condensing)		10% to 95%
Mechanical construction		
Dimensions (W x H x D)		480 mm x 88 mm x 435 mm
Mounting		19" control cabinet
Weight		7.5 kg
Protection class		IP 20
Mechanical stability		
IEC 60068-2-27 shock		15 g, 11 ms duration, 18 shocks

Industrial Ethernet:Backbone Switches:Chassis:MACH4002-48G+3X-L3P
<http://www.e-catalog.beldensolutions.com/link/57078-24455-49838-24526-40297/en/conf/ui:state>

IEC 60068-2-6 vibration	1 mm, 2 Hz - 13.2 Hz, 90 min.; 0.7 g, 13.2 Hz - 100 Hz, 90 min.; 3.5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz - 150 kHz), 10 V (150 kHz - 80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC CFR47 Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508
Shipbuilding	Germanischer Lloyd
Safety of information technology equipment	cUL 60950-1
Railway norm	EN50121-4 (pending)
Scope of delivery and accessories	
Scope of delivery	device, terminal block, operating manual, fan M4-AIR installed
Accessories to order separately	SFP transceiver (100/1000MBit/s), Power supply unit, auto-configuration adapter (ACA21-USB), network management with Industrial HiVision

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect.
 The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.