


Product information

RPS 60

Fiber Interfaces:Archive - Fiber Interfaces:Accessories Fiber Interfaces:DIN Rail Power Supplies:RPS 60

<http://www.e-catalog.beldensolutions.com/link/57078-57141-57328-57139-24574-38633/en/conf/uistate>

Name	RPS 60
	
	DIN rail power supply
Delivery informations	
Availability	available
Product description	
Description	DIN rail power supply
Type	RPS 60
Order No.	943 662-001
Ambient conditions	
Operating temperature	-10 °C to +70 °C (from 60 °C derating)
Storage/transport temperature	-25 °C to +85 °C
Relative humidity (non-condensing)	10% to 90%
Mechanical construction	
Dimensions (W x H x D)	50 x 125 x103 mm
Mounting	DIN rail
Weight	460 g
Protection class	IP 20
EMC interference immunity	
EN 50082-1	??????????
EN 50082-2	??????????
EMC emitted immunity	
EN 50081-1	??????????
EN 50081-2	??????????
Scope of delivery and accessories	
Scope of delivery	device, operating instructions

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.