

CCH Cassette

Splicing, empty, for 1 CCH panel

CORNING

CCH cassettes enable fast field termination and easy modular management of connectorization within the housing.

The CCH Splicing Cassette supports fusion splicing of individual or ribbon fibers, with heat shrinks, pigtail slack and cable slack managed within a single space saving footprint. This eliminates the need for individual splice trays or separate splice housings, as well as allowing splicing to be done away from the rack housing in a suitable workspace as needed. The modular design makes it easy to access the fiber in an individual cassette without disturbing the other fibers in the housing. A CCH panel with the desired adapter configuration can be ordered separately and fits easily into the cassette.

A CCH Slack Cassette option with no splice tray, suitable for use with field-installable connectors, is also available.

Each cassette is shipped with 1 rail for use with CCH-01U/2U/3U housings, and 2 rails used with CCH-04U housings. Grommets and cable ties for strain relief, and protective braided tubing for incoming cable are also included. Splicing cassettes ship with 12 single fiber heat-shrink splice protectors.



Part Number: CCH-CS

Features and Benefits

Manage cable slack for a CCH Panel in a modular footprint

Fast, easy and reliable initial routing, and quick, simple reaccess for moves, adds and changes (MACs)

Splicing Cassette holds 24 single fiber splices

Splice to full housing capacity, and manage all splices inside the housing

Includes everything needed to convert a CCH housing for modular routing and/or splicing

Easy ordering and field installation

Standards

Approval and Listings

Meets ANSI/TIA/EIA-568A and 606

CORNING

CCH Cassette

Splicing, empty, for 1 CCH panel



Specifications

General Specifications	
Application	Enterprise Networks, Data Center
Product Type	Rack-Mountable Hardware
Mounting Type	Rack 19-in, Rack 23-in, Wall-Mountable
Technology	Fusion Splice

Design - Hardware	
Splice Protectors Type	Heat-shrink
Splice Tray Capacity Single Fiber	24 Splices
Splice Tray Capacity Mass Fusion	6 Splices
Panel or Module Type	CCH

Mechanical Characteristics	
Dimensions (LxWxD)	6.4 in x 1.4 in x 7.9 in 162.0 mm x 35.0 mm x 200.0 mm

Chemical Characteristics	
RoHS	Free of hazardous substances according to RoHS 2002/95/EG

Ordering Information

Part Number	CCH-CS
Product Description	CCH Cassette, Splicing, empty, for 1 CCH panel

Shipping Information

Units per Delivery	1/1
--------------------	-----

CCH Cassette

Splicing, empty, for 1 CCH panel

The CORNING logo is a blue square with the word "CORNING" in white, uppercase, sans-serif font centered inside.

Notes



Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/cablesystems

A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/trademarks.

Corning Cable Systems is ISO 9001 certified. © 2012 Corning Cable Systems. All rights reserved.