

Pretium EDGE® Solutions Tap Module

50 µm MM (OM4), 70/30 split ratio (live/tap), 12-F LC duplex ports, one pinned MTP® adapter labeled LIVE, one pinned red MTP® adapter labeled TAP

CORNING

Pretium EDGE® Tap Modules, part of Pretium EDGE Solutions for data centers and storage area networks, enable passive optical tapping of the network while reducing downtime and link loss, and while increasing rack space utilization and density compared to other optical tap options. Unlike other passive optical taps that must be added as a separate device in the network link, the Pretium EDGE Tap Module integrates the coupler technology for passive optical tapping into a structured cabling component--the module. Monitored ports can be added without disrupting the system's live traffic, and elimination of the tap as a separate device reduces insertion loss in the link.

Pretium EDGE® Tap Modules use an advanced splitter technology for multimode to reduce insertion loss compared to traditional splitter technology. Featuring the Pretium EDGE Solutions high-density module footprint, Pretium EDGE Tap Modules enable up to 72 monitored links per 1 rack unit, and they fit seamlessly into Pretium EDGE Solutions hardware for maximum cable management and better utilization of rack space.



Part Number: ETM-7B-Q

Features and Benefits

Integrates tap splitters directly into the structured cabling infrastructure

Eliminates network downtime associated with changing monitored ports in a live system

Rear-exiting, MTP® based TAP ports do not require additional rack space

Zero rack space impact results in higher revenue generation per rack unit; allows separation of live and tap ports into different cabinet locations

Utilizes advanced splitter technology

Maintains equal modal power distribution, reducing insertion loss for increased link reach

Pretium EDGE®-based footprint

Integrates seamlessly into an existing Pretium EDGE Solutions infrastructure

Universal polarity management

Eliminates the frustration of needing to flip connector pairs or modules

Pretium EDGE® Solutions Tap Module

50 µm MM (OM4), 70/30 split ratio (live/tap), 12-F LC duplex ports, one pinned MTP® adapter labeled LIVE, one pinned red MTP® adapter labeled TAP

CORNING

Specifications

General Specifications

Application	Data Center LAN/SAN
Product Type	Panels & Modules
Fiber Category	50 µm MM (OM4)

Design - Hardware

Fiber Count	12
Number of Adapters per Panel	6
Adapter Type Front	Shuttered LC
Adapter Color Front	Aqua
Adapter Type Back	MTP®
Adapter Color Back	Aqua/Red

Mechanical Characteristics

Dimensions (HxWxD)	12 mm x 90 mm x 165 mm (0.463 in x 3.53 in x 6.50 in)
--------------------	---

Optical Specification - Hardware

MTP® Connector Insertion Loss	0.35 dB
LC Connector Insertion Loss	0.15 dB
Splitter Loss for Tap Modules	1.8 dB LIVE / 6.6 dB TAP

Design - Connector A

Connector Type	LC duplex
Ferrule	Ceramic

Design - Connector B

Connector Type	MTP® (pinned)
Ferrule	Composite

Pretium EDGE® Solutions Tap Module

50 µm MM (OM4), 70/30 split ratio (live/tap), 12-F LC duplex ports, one pinned MTP® adapter labeled LIVE, one pinned red MTP® adapter labeled TAP

CORNING

Cable Design

Polarity	Universal
----------	-----------

Ordering Information

Part Number	ETM-7B-Q
-------------	----------

Product Description	Pretium EDGE® Solutions Tap Module, 50 µm MM (OM4), 70/30 split ratio (live/tap), 12-F LC duplex ports, one pinned MTP® adapter labeled LIVE, one pinned red MTP® adapter labeled TAP
---------------------	---

Shipping Information

Units per Delivery	1/1
--------------------	-----

Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/cablesystems

A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/trademarks. Corning Cable Systems is ISO 9001 certified. © 2012 Corning Cable Systems. All rights reserved.