

FDC® Unit Connector Housings

An Evolant™ Solutions Product

Corning
Cable Systems


Description

Corning Cable Systems' Connector Housings provide inter-connect or cross-connect capabilities between the outside plant (OSP) riser or distribution cables and the opto-electronics. The connector housings can be rack-mounted in standard 19-in (48 cm) or 23-in (58.4 cm) equipment racks and are available in a variety of fiber capacities.


Connector housings can be ordered with loaded adapter panels or preconnectorized panels or modules for both multimode and single-mode applications. Multiple units can be added as needed to construct a fiber distribution frame for high-fiber-count applications. Labels are provided for documentation.

Features / Benefits

- 19-in or 23-in rack-mount option or wall-mountable with optional kit
- Used as a component of Corning Cable Systems' Fiber Distribution Frame
- Field-connectorization or pigtail splicing in conjunction with Splice Module Housings
- Suitable for loose tube, tight-buffered and ribbon cables
- Frontal projection of 4.25 in (10.8 cm) or flush-mounted with an optional kit
- Smoke-tinted front door, removable hinged front and rear doors
- Accepts Corning Cable Systems FDC® unit connector panels, jumper storage modules and connector modules
- Front and rear door slide latches for easier access
- Flipcard for easier record keeping
- Larger routing guides for better jumper management
- More open design for easier connector access



FDC-CMH-072 Equipped with Optional
6-Fiber SC Panels | Drawing CPC-220/5/22



FDC-CMH-096 Equipped with Optional
8-Fiber SC Panels | Drawing CPC-220/5/23

Specifications and Ordering Information

Part Number	Description	Dimensions (H x W x D) in (cm)	Shipping Weight lb (kg)
Connector Housings – Empty			
FDC-CMH-024	FDC® Unit Connector Housing; accepts four 6-in panels or modules or eight jumper storage modules	5.2 x 17.0 x 11.0 (13.3 x 43.2 x 28.0)	14.0 (6.3)
FDC-CMH-072*	FDC Unit Connector Housing; accepts 12 6-in panels or modules or 24 jumper storage modules	8.7 x 17.0 x 11.0 (22.2 x 43.2 x 28.0)	15.0 (6.8)
FDC-CMH-096	FDC Unit Connector Housing; accepts 12 7.5-in panels (FDC-CP8P) or modules (FDC-CP18) only	8.7 x 17.0 x 11.0 (22.2 x 43.2 x 28.0)	15.0 (6.8)
FHC-CMH-144	FDC Unit Connector Housing; accepts 12 7.5-in, 12-fiber panels – SC, FC only	8.7 x 17.0 x 11.0 (22.2 x 43.2 x 28.0)	15.0 (6.8)

* Note: The FDC-CMH-072 may be configured for 144 fibers using 12-fiber FDC unit panels and SC connectors only.

Connector Housings – with Adapters

FDC - CMH - 72	<input type="checkbox"/> <input type="checkbox"/> 1	72-fiber capacity FDC Unit Housing (FDC-CMH-072) with 12 6-fiber panels equipped with specified adapter type
FDC - CMH - 96	<input type="checkbox"/> <input type="checkbox"/> 1	96-fiber capacity FDC Unit Housing (FDC-CMH-096) with 12 8-fiber panels equipped with specified adapter type
FDC - CMH - E4	<input type="checkbox"/> <input type="checkbox"/> 1	144-fiber capacity FDC Unit Housing (FDC-CMH-072) with 12 12-fiber panels (available with SC adapter types only)
FD5 - CMH - 24	<input type="checkbox"/> <input type="checkbox"/> 1	24-fiber capacity FDC Unit Housing (FDC-CMH-024) with four 6-fiber panels equipped with specified adapter type

1 Select adapters.

ST® Compatible

- 15 = ST compatible, ceramic insert, multimode, composite housing
- 15T = ST compatible, ceramic insert, multimode, composite housing, threaded bulkhead mount
- 19 = ST compatible, ceramic insert, single-mode, composite housing
- 19T = ST compatible, ceramic insert, single-mode, composite housing, threaded bulkhead mount
- 25 = ST compatible, composite insert, multimode, composite housing
- 25T = ST compatible, composite insert, multimode, composite housing, threaded bulkhead mount

SC

- 38 = SC, phosphor bronze insert, single-mode
- 3C = SC, ceramic insert, single-mode
- 39 = SC, phosphor bronze insert, multimode
- 56 = SC, composite insert, multimode
- 6C = SC, for Angled Polish Connectors (APC), ceramic insert, single-mode

SC Duplex

- 57 = 568SC (SC duplex), phosphor bronze insert, multimode, plastic housing
- 59 = 568SC (SC duplex), ceramic insert, single-mode, plastic housing
- 91 = 568SC (SC duplex), composite insert, multimode, plastic housing

MT-RJ

- 97 = MT-RJ multimode
- 98 = MT-RJ single-mode

Ordering Information (continued)

Accessories

Part Number	Description
Jumper Storage Modules	
FDC-JSM	Set of two Jumper Storage Modules to fit FDC-CMH-072 or FDC-CMH-024 (each set of two fills the space of one connector panel or module); 5-meter slack capacity per module
FDC-JSH-24	8.75-in-tall (22.2 cm) Jumper Storage Housing; includes 24 individual jumper storage modules; 5-meter slack capacity per module
Additional Items	
FD5-WALLBKT	Wall Mounting Kit for 5.25-in-tall housings
FDC-CMH-WALLBKT	Wall Mounting Kit for 8.75-in-tall housings
FDC-FLSHMNT-SM	Flush Mounting Kit for 5.25-in-tall housings
FDC-FLSHMNT-LG	Flush Mounting Kit for 8.75-in-tall housings
FDC-FRTDR-LX-L	Front Door with Lock Kit, plastic door, for 8.75-in-tall housings
FDC-FRTDR-MT-L	Front Door with Lock Kit, metal door, for 8.75-in-tall housings
FDC-SIDEPNL-LG	Side Panels to enclose 8.75-in FDC® unit housing; kit includes two panels
FDC-SIDEPNL-SM	Side Panels to enclose 5.25-in FDC unit housing; kit includes two panels
FDC-UCC	Universal Cable Clamp Kit with FDC unit mounting bracket
FDC-PNL-KIT	Kit for -072 to -096 conversion or vice versa
FD5-FRTDR-LX-L	Front Door with Lock Kit, plastic door, for 5.25-in-tall housings
FD5-FRTDR-MT-L	Front Door with Lock Kit, metal door, for 5.25-in-tall housings

FDC® Unit Connector Housings

An Evolant™ Solutions Product

Corning
Cable Systems



CORNING
Discovering Beyond Imagination

Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA

1-800-743-2675 • FAX: +1-828-901-5973 • International: +1-828-901-5000 • <http://www.corning.com/cablesystems>

Corning Cable Systems reserves the right to improve, enhance and modify the features and specifications of Corning Cable Systems' products without prior notification. FDC is a registered trademark of Corning Cable Systems Brands, Inc. Evolant is a trademark of Corning Cable Systems Brands, Inc. Discovering Beyond Imagination is a trademark of Corning Incorporated. ST is a registered trademark of Lucent Technologies. All other trademarks are the properties of their respective owners. Corning Cable Systems is ISO 9001 certified. © 2003 Corning Cable Systems. All rights reserved. Published in the USA. EVO-246-EN / January 2003 / 7M