## Lightguide Distribution Center (LDC) Housing, LGX<sup>®</sup> Compatible


7-in, 24 F, order connector panels separately



Corning Cable Systems offers a variety of LDC termination products that include adapter housings, stubbed housings, panels and modules. This family of Corning Cable Systems hardware is fully frame compatible with Lucent LGX® frames and components.

LDC connector housings provide interconnect and cross -connect capabilities between the outside plant, riser or distribution cables and the opto-electronics. The housings can be wall- or rack-mounted in 19- or 23-in equipment racks and are available in a variety of connector capacities.

The housings include hardware so they can be mounted to the front or rear of the rack rails or flush mounted to the wall. They are also equipped with standard 12.7 cm (5 in) frontal projection with optional 10.79 cm (4.25 in). These housings can be ordered empty, preloaded with adapter panels or modules, or with a factory-installed cable stub or pigtails.



#### Features and Benefits

LGX® Compatible

Simplifies installation

Accommodates popular adapter types

Reduces inventory

Universal cable clamp (UCC-001)

Additional enhanced cable strain-relief

## **Specifications**

General Specifications	
Application	Central Office, Carrier Networks, CATV environments
Mounting Type	Rack 19-in, Rack 23-in
Product Type	Rack-Mountable Hardware



# Lightguide Distribution Center (LDC) Housing, LGX<sup>®</sup> Compatible

7-in, 24 F, order connector panels separately



Design - Hardware	
Housing Type	LDC
Housing Color	Platinum
Panel or Module Type	LDC

Mechanical Characteristics	
Dimensions (HxWxD)	17.8 cm x 43.2 cm x 27.9 cm (7 in x 17 in x 11 in)

#### **Ordering Information**

Part Number	LDC-CMH-072
Product Description	Lightguide Distribution Center (LDC) Housing, LGX® Compatible, 7-in, 24 F, order connector panels separately

### **Shipping Information**

Units per Delivery	1/1
Shipping Weight	4.4 kg (9.8 lb)

Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA 800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/cablesystems

A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/trademarks.

Corning Cable Systems is ISO 9001 certified. © 2012 Corning Cable Systems. All rights reserved.

