# Splice Tray, Heat-shrink Fusion Splices

Wide, 0.4-in, 12 F



Corning Cable Systems splice trays use proven designs and fiber organization technology to provide optimum physical protection for fusion and mechanical splicing methods. The trays are engineered for use with indoor or outdoor splice hardware with both loose tube and tight-buffered optical cable designs.

The metal-tray series consists of a rugged aluminum base and cover with crimpable metal tabs for buffer tube strain-relief. Additional strain-relief points are available for securing buffer tubes or pigtails to the trays using cable ties. The black powder coating allows easy fiber identification and additional protection. Designed for use with Corning Cable Systems interconnection hardware and splice closures, these splice trays are an integral part of a complete splicing system.

Many of our fiber optic hardware products are highly configurable. If you don't see what you are looking for here, please review the ordering matrix contained in the family spec sheet found on the right, or contact customer care at 1-800-743-2671.

#### Features and Benefits

Metal trays powder coated

Ruggedness and durability

Clear plastic covers

Fiber visibility for inspection

Fiber loop retention

Controls the bend-radius

Positive holding action
Maximum splice protection

Specifications

# General Specifications Application Central Office, CATV environments, Carrier Networks, Enterprise Networks Product Type Splice Trays Technology Fusion Splice



# **Splice Tray, Heat-shrink Fusion Splices**

Wide, 0.4-in, 12 F



| Design - Hardware                 |  |
|-----------------------------------|--|
| Splice Protectors Type            | Heat-shrink  |
| Splice Tray Category              | 4S   |
| Splice Tray Type                  | Standard with organizers for heat-shrink fusion splice protect ors |
| Splice Tray Capacity Single Fiber | 24 Splices   |

| Mechanical Characteristics |  |
|----------------------------|--|
| Dimensions (LxWxD)         | 11.7 in x 3.9 in x 0.2 in297 mm x 99 mm x 5 mm |
|                            |  |

| Chemical Characteristics |   |
|--------------------------|---|
| RoHS                     | Free of hazardous substances according to RoHS 2002/95/<br>EG |
|                          |   |

### **Ordering Information**

| Part Number         | M67-078   |
|---------------------|---|
| Product Description | Splice Tray, heat-shrink fusion splices, wide, 0.4-in, 12 F |

## **Shipping Information**

| Units per Delivery | 1/1  |
|--------------------|--|
| Package Contents   | Installation Guide; splice tray base with splice holder; splice tray cover |



Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA 800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/cablesystems

A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/trademarks.

Corning Cable Systems is ISO 9001 certified. © 2012 Corning Cable Systems. All rights reserved.

