

Fiber Optic Cleaning Tool Kit

Single-fiber connectors

CORNING

Corning Cable Systems Single-Fiber Connector Cleaning Kit is designed for effective cleaning of fiber optic connector end-faces, whether fully accessible or in an adapter, in local area network (LAN), central office and outside plant environments. Whether performing a 'dry' clean, 'wet' clean or a combination of the two, each kit offers all the products recommended for cleaning connectors. Since electrostatic discharge (ESD) is a concern during a 'dry' clean, this kit contains cleaners specifically formulated to dissipate static when the end-face is pulled across a cleaner surface or a stick inserted into an adapter.

Features and Benefits

Solvents are non-hazardous and ozone-safe
Shippable by air

Contains product for 'wet' and 'dry' cleaning
Convenience and versatility

Cleaners for 'dry' clean dissipate static
Addresses electrostatic discharge (ESD) concerns



Specifications

General Specifications	
Product Type	Accessories
Packaging	Individual Packaging

Mechanical Characteristics	
Dimensions (HxWxD)	22.86 cm x 31.75 cm x 15.24 cm (9 in x 12.5 in x 6 in)
Weight	1.6 kg (0.73 lb)

Chemical Characteristics	
RoHS	Free of hazardous substances according to RoHS 2002/95/EG

Fiber Optic Cleaning Tool Kit

Single-fiber connectors



Ordering Information

Part Number	TKT-CLEAN-SFC
Product Description	Single-fiber connector cleaning kit contains recommended products to effectively clean 2.5 mm and 1.25 mm single-fiber connectors.

Shipping Information

Units per Delivery	1/1
Package Contents	Cleaning fluid, cleaning wipes, 1.25 mm cleaning sticks, 2.5 mm cleaning sticks, carrying case



Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/cablesystems

A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/trademarks.

Corning Cable Systems is ISO 9001 certified. © 2012 Corning Cable Systems. All rights reserved.

