Wall-Mountable Interconnect Center (WIC), Lanscape

Holds 2 CCH connector panels

CORNING

Corning Cable Systems Wall-Mountable Interconnect Center (WIC) is a cost-effective unit designed for storage and protection of fiber-optic connections. This compact, modular unit is ideal for use in locations such as building entrance terminals, wiring closets, open office and other controlled environments where space is at a premium.

Features and Benefits

Universal cable clamp Cable strain-relief

Durable metal housing Protection

Lockable doors System security

Routing guides Fiber management



Specifications

General Specifications	
Application	Enterprise Networks
Mounting Type	Wall-Mountable
Product Type	Wall-Mountable Hardware

Design - Hardware	
Housing Color	Black
Housing Type	WIC
Locking Availability	Provider door
Maximum Number of Panels per Housing	2
Panel or Module Type	CCH
Splice Tray Options	Up to (4) 0.2-in or (2) 0.4-in reduced-length splice trays

Mechanical Characteristics	
Dimensions (HxWxD)	33 cm x 21.6 cm x 6.6 cm (13 in x 8.5 in x 2.6 in)



Wall-Mountable Interconnect Center (WIC), Lanscape

Holds 2 CCH connector panels

CORNING

Chemical Characteristics	
RoHS	Free of hazardous substances according to RoHS 2002/95/ EG

Ordering Information

Part Number	WIC-02P
Product Description	Wall-Mountable Interconnect Center (WIC), holds 2 CCH con- nector panels

Shipping Information

Units per Delivery	1/1
Package Contents	Housing; blank panel; instruction sheet; central member strain-relief clamp kit; 6 tie wraps, 1/8 x 4, white; neoprene edge grommeting, 6-in
Shipping Weight	2.3 kg (5 lb)



Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA 800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/cablesystems A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/trademarks. Corning Cable Systems is ISO 9001 certified. © 2012 Corning Cable Systems. All rights reserved.

