

PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 921015 **DESCRIPTION:** RG-6/U PLENUM COAXIAL CABLE WITH FOIL AND 80% BRAID SWEPT TO 3.0 GHZ

RATING:

C(ETL)US LISTED AS CMP/CL2P FT6

Construction Parameters:

| | | Wall (in)* | <u>OD (in)*</u> |
|-------------|--|------------|-----------------|
| Conductors: | 18 AWG (1/.040) Copper Clad Steel | | 0.040 |
| Dielectric: | Foam FEP color natural | 0.065 | 0.170 |
| Shielding: | Aluminum/Polyester/Aluminum Foil with 80% Aluminum Braid | | 0.194 |
| Jacket: | Low Smoke PVC | 0.021 | 0.235 |

Electrical Properties:

| | | VALUE* |
|----------------------------|----------|--------|
| Conductor Resistance (ol | 16.3 | |
| Impedance (ohms): | 75 | |
| Capacitance (pF/ft): | 16.5 | |
| Velocity of Propagation (9 | 82 | |
| Attenuation (db/100 ft): | 50 MHz | 1.5 |
| | 100 MHz | 1.9 |
| | 200 MHz | 3.2 |
| | 400 MHz | 4.2 |
| | 700 MHz | 6.4 |
| | 1000 MHz | 6.9 |
| | 1500 MHz | 9.4 |
| | 2000 MHz | 11.1 |
| | 2200 MHz | 11.8 |
| | 3000 MHz | 17.0 |

Cable Cross-section: (NOT TO SCALE)



Miscellaneous Information:

| Jacket Color: | Natural |
|---------------------------|--|
| Jacket Print (Teal/Aqua): | COLEMAN CABLE 921015 RG6 18 AWG CCS DUAL SHIELD 80% AL BRAID |
| ASCENDING/DESCENDING | C(ETL)US 3020464 CMP OR CL2P FT6 75C SWEPT TO 3.0 GHZ |
| FOOTAGE MARKING | |
| Applicable NEC Article: | 725 & 800 |
| Temperature Rating: | 75C |
| Flame Rating: | UL 910 Steiner Tunnel Smoke and Flame Test |
| 0 | CSA FT6 Horizontal Flame and Smoke Test |
| | |

Approx. Weight (lb/1000 ft): 42

This product complies with European Directive 2002/95/EC (RoHS) On special orders the customer will accept all factory lengths and \pm 10% of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product (s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise

Company Name:

Customer Approval:

09/20/06

Issued:

Date:

* = Nominal value By: PMV