## FutureCom™ Module Housing, 25 x 38 mm, inclined, for 1 x FutureCom module

White



The LANscape® FutureCom™ module adapter inclined is suitable for the installation of LANscape FutureCom modules. The module adapter 25 x 38 mm with self-closing shutter is intended for the direct assembly into cable raceways. Holders for cable tray are not intended, because the module housing can be in-clicked directly into the cable raceway. Designation windows with designation stripes are included.

#### **Features**

- Self-closing shutter
- Designation window



#### **Specifications**

General Specifications	
Halogen-free	Yes
Dust protection	Yes

Temperature Range	
Installation and assembly	-20 °C to 70 °C

Design - Hardware	
Number of Ports	1
Colour	white, RAL 9010

Mechanical characteristics	
Dimensions (L x W)	25 mm x 38 mm



# FutureCom™ Module Housing, 25 x 38 mm, inclined, for 1 x FutureCom module

White



Chemical characteristics	
RoHS	Free of hazardous substances according to RoHS 2002/95/EG
Environmental compatibility	Recyclable

### **Ordering Information**

Part Number	CAXCSE-S0101-C002
Product Description	Module housing 25 x 38 mm, inclined , with self-closing shutter for installation of one FutureCom $^{\text{TM}}$ module, designation window *Not suited for connectors requiring the FutureCom Adapter or LANS/LANC adapter modules (S1200 Connector, Fiber Optic Adapters)
Weight	16 g

### **Shipping Information**

Units per Delivery	1/1



Corning Cable Systems GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, Germany TEL: 00800-2676-4641 (00800-CORNING1) · FAX: +49-30-5303-2335 · www.corning.com/cablesystems/emea

A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/emea/trademarks. Corning Cable Systems is ISO 9001 certified. © 2013 Corning Cable Systems. All rights reserved.

