

# Closet Connector Housing (CCH)

2 rack units, holds 4 CCH connector panels

CORNING

Designed based on thousands of hours of customer feedback, Corning Cable Systems Closet Connector Housings (CCHs) offer more than two dozen innovative features that make installation and troubleshooting of fibre optic connectivity faster, easier and more cost effective.

From fibre and cable routing and strain relief, to port labelling and termination, these housings reduce the risk of error that can disrupt networks.

Closet Connector Housings (CCHs) provide interconnect or cross-connect capabilities between outside plant, riser or distribution cables and opto-electronics. Like other LANscape Solutions hardware, the housings accept CCH connector panels. In addition, the housings accept CCH cassettes and CCH modules.

The units are designed for rack mounting in 19-in (48 cm) racks or optional 23-in (58 cm) equipment racks (1.75-in EIA hole spacing). They are available in rack space options of 1U (two panels, cassettes or modules), 2U (four panels, cassettes or modules), 3U (six panels, cassettes or modules) and 4U (twelve panels, cassettes or modules). The 1U, 2U and 3U options feature a slide-out tray and see-through, removable top covers. The CCH-04U features a clear door, removable front and rear enclosures and a platinum-painted interior for maximum visibility and access.

Every CCH housing is shipped complete with strain relief brackets, routing clips and guides, and mounting brackets for proper installation. Documentation labels are provided and components can be added as needed to construct a fibre distribution frame for any application. All housings include a removable tinted polycarbonate front door. All size housings have field-installable lock kits available for both front and rear doors.

All CCH housings can also be upgraded for pigtail splicing to full fibre capacity and easy, modular fibre management through the use of CCH Splice Cassettes (CCH-CS), or for easy, modular fibre management when using field-installable connectors through the use of CCH Slack Cassettes (CCH-CF).



Part Number: CCH-02U

## Features and Benefits

### Interconnect and cross-connect capability

Ideal for field connectorization

### Removable, translucent top covers (1U, 2U, 3U), removable rear cover (4U)

Visibility and ease of access for installation, testing and troubleshooting

# Closet Connector Housing (CCH)

2 rack units, holds 4 CCH connector panels

CORNING

## Features and Benefits

### Internal and external strain-relief options

Flexibility for installation and moves, adds and changes (MACs)

### Accepts panels, modules and cassettes

Variety of field termination options

### Adaptable to use as a modular splice housing

Splices are stored and protected in same footprint

## Standards

### Approval and Listings

Meets ANSI/TIA/EIA-568A and 606

### RoHS

Free of hazardous substances according to RoHS 2002/95/EG

### UL-Listed

## Specifications

General Specifications	
Application	Enterprise Networks, Data Centre, Carrier Networks
Mounting Type	Rack 19", Rack 23"
Product Type	Fibre Optic Hardware
Environment	Indoor
Mounting Technology	Flush mount, Protruding, Recessed
Access Type	Front and rear access slidable
Lockable	Yes

# Closet Connector Housing (CCH)

2 rack units, holds 4 CCH connector panels

CORNING

## Design - Hardware

Housing Type	CCH
Housing Colour	Black
Height Unit	2U
Locking Availability	Front or rear
Number of Panels per Housing	4
Panel or Module Type	CCH
Splice Tray Options	CCH Splice Cassette (CCH-CS)

## Mechanical characteristics

Dimensions (HxWxD)	8.9 cm x 48.3 cm x 43 cm (3.5 in x 19 in x 17 in)
--------------------	---

## Ordering Information

Part Number	CCH-02U
Product Description	Closet Connector Housing (CCH), 2 rack unit, holds 4 CCH connector panels

## Shipping Information

Units per Delivery	1/1
Shipping Weight	5.4 kg (12 lb)
Dimensions (HxWxD)	54.61 cm x 57.15 cm x 19.05 cm (21.5 in x 22.5 in x 7.5 in)



Corning Cable Systems GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, Germany

TEL: 00800-2676-4641 (00800-CORNING1) · FAX: +49-30-5303-2335 · [www.corning.com/cablesystems/emea](http://www.corning.com/cablesystems/emea)

A complete listing of the trademarks of Corning Cable Systems is available at [www.corning.com/cablesystems/emea/trademarks](http://www.corning.com/cablesystems/emea/trademarks). Corning Cable Systems is ISO 9001 certified. © 2013 Corning Cable Systems. All rights reserved.