
## CADDY® CAT HP J-Hook Tree, Ceiling Mount – CAT64HPSCM3 (181054)









- Ideal for attaching to concrete, steel or wood surfaces
- Provides optimal support for high-performance data cable, up to and including Cat 5e, Cat 6, Cat 6A, Cat 7 and fibre optic
- Ready to use out of the box, saving installation time and labor
- Requires no screws, rivets or special tools for assembly
- Single- or double-sided tree configurations provide multiple J-Hooks with one structural attachment
- Provides superior fill capacity and load rating over most other non-continuous cable support alternatives
- Meets ISO®/IECSM 14763-2, TIASM 568-C and TIASM 569-C









| Part Number       | CAT64HPSCM3       |
|-------------------|-------------------|
| Article Number    | 181054            |
| Material          | Steel             |
| Finish            | Pre-galvanized    |
| Туре              | Single Sided      |
| Diameter (Ø)      | 4"<br>100 mm      |
| Tiers             | 3                 |
| Height (H)        | 22 3/4"<br>578 mm |
| Width (W)         | 5 7/16"<br>138 mm |
| Hole Size 1 (HS1) | 0.405"<br>10.3 mm |
| Hole Size 2 (HS2) | 0.185"<br>4.7 mm  |
| А                 | 1 7/16"           |





| Part Number                 | CAT64HPSCM3     |
|-----------------------------|-----------------|
|                             | 36.5 mm         |
| В                           | 2"<br>50 mm     |
| Static Load 1 (F1)          | 180 lb<br>810 N |
| Static Load 2 (F2)          | 180 lb<br>810 N |
| Standard Packaging Quantity | 5 pc            |
| UPC                         | 78285679933     |
| UNSPSC                      | 39131709        |
| Approvals                   | cULus®          |

Static loads represent maximum load limit of J-Hook tree. Static load limit of each J-Hook is 60 lb (270 N). Refer to Static Load 1 when fastening J-Hook tree using Hole Size 1. Refer to Static Load 2 when fastening J-Hook tree using Hole Size 2. Non-continuous supports may not exceed spacing of 5' (1.5 m) per TIA<sup>SM</sup> 569-C.9.7.

cULus is a registered certification mark of UL LLC. IEC is a registered service mark of Independent Electrical Contractors, Inc. ISO is a registered trademark of International Organization for  $Standardization. \ TIA \ is \ a \ registered \ service \ mark \ of \ the \ Telecommunications \ Industry \ Association.$ 

## WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2013 ERICO International Corporation. All rights reserved. CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.



