

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20

Flexible Cables and Cords

LSZH Insulated and Sheathed Flexible Cords H05Z1Z1-F

70°C 300/500 V 318*B



Application

For external supply connection of portable appliances for medium duties in domestic or office environments.

* denotes number of cores.

Specifications

- In accordance with BS EN 50525-3.11 and meeting Harmonised code H05Z1Z1-F
- **Conductors:** Flexible Class 5 conductors to BS EN 60228
- **Insulation:** LSZH insulation Type Tl.6 to HD 21.14 S1
- **Core Identification:**
 - 2 core - blue, brown
 - 3 core - green/yellow, blue, brown
 - 4 core - green/yellow, brown, black, grey
 - 5 core - green/yellow, brown, black, grey, blue
- **Sheath:** LSZH sheath Type TM.7 to HD 21.14 S1 (white)
- Flame retardant to BS EN 60332-1-2
- **Temperature Rating:** 70°C maximum conductor operating temperature
- **Voltage Rating:** 300/500 V

LSZH Insulated and Sheathed Flexible Cords H05Z1Z1-F

70 °C 300/500 V 318*B

Anixter Number	Nominal Conductor Area	Nominal Conductor Stranding	Insulation Thickness	Minimum O/D	Maximum O/D	Approximate Cable Weight
		mm ²	#/mm	mm	mm	mm
Twin Core Type 3182B						
3182B-0007-##	0.75	24/0.20	0.6	5.7	7.2	63
3182B-0010-##	1.0	32/0.20	0.6	5.9	7.5	73
3182B-0012-##	1.25	40/0.20	0.7	6.3	8.0	84
3182B-0015-##	1.5	30/0.25	0.7	6.8	8.6	95
3182B-0025-##	2.5	50/0.25	0.8	8.4	10.6	145
3182B-0040-##	4.0	56/0.30	0.8	10.1	12.0	200
Three Core Type 3183B						
3183B-0007-##	0.75	24/0.20	0.6	6.0	7.6	74
3183B-0010-##	1.0	32/0.20	0.6	6.3	8.0	86
3183B-0012-##	1.25	40/0.20	0.7	6.9	8.7	104
3183B-0015-##	1.5	30/0.25	0.7	7.4	9.4	120
3183B-0025-##	2.5	50/0.25	0.8	9.2	11.4	180
3183B-0040-##	4.0	56/0.30	0.8	11.0	13.0	250
Four Core Type 3184B						
3184B-0007-##	0.75	24/0.20	0.6	6.6	8.3	78
3184B-0010-##	1.0	32/0.20	0.6	7.1	9.0	110
3184B-0015-##	1.5	30/0.25	0.7	8.4	10.5	150
3184B-0025-##	2.5	50/0.25	0.8	10.1	13.0	220
3184B-0040-##	4.0	56/0.30	0.8	12.0	14.0	305
Five Core Type 3185B						
3185B-0007-##	0.75	24/0.20	0.6	7.4	9.3	98
3185B-0010-##	1.0	32/0.20	0.6	7.8	9.8	118
3185B-0015-##	1.5	30/0.25	0.7	9.3	11.6	180
3185B-0025-##	2.5	50/0.25	0.8	11.2	13.9	265
3185B-0040-##	4.0	56/0.30	0.8	13.5	15.5	380

= sheath colour, -01 = white, -02 = black.
Other colours available upon request.

For further technical information see page 2:44.

Technical Specifications for Flexible Cords

Applicable to: 2491X, 218*Y, 318*Y, 309*Y, 318*B, 318*P, 318*TQ, 398*P
H05V-K, H03V-F, H05VV-F, H05V2V2-F, H05Z1Z1-F, H05RN-F, H05BN4-F, H07RN-F

CORRECTION FACTOR FOR AMBIENT TEMPERATURE

60°C rubber and PVC cords:

Ambient air temp °C	35	40	45	50	55
Rating factor	0.91	0.82	0.71	0.58	0.41

90°C rubber cords having a HOFR sheath or a heat-resisting PVC sheath and for 90°C heat-resisting PVC cords:

Ambient air temp °C	35 - 50	55	60	65	70
Rating factor	1.0	0.96	0.83	0.67	0.47

180°C rubber cords:

Ambient air temp °C	35 - 150	155	160	165	170	175
Rating factor	1.0	0.92	0.82	0.71	0.57	0.40

For cables where four or more cores or loaded, the following factors should be applied:

No. of cores loaded	4	5	6	7	10	12	14	19	24
Rating factor	0.78	0.72	0.67	0.63	0.56	0.53	0.51	0.45	0.42
No. of cores loaded	27	30	37	-	-	-	-	-	-
Rating factor	0.40	0.39	0.36	-	-	-	-	-	-

These factors need not be applied if the number of cores loaded does not exceed the square root of the total number of cores in the cable.

Technical Specifications for Flexible Cords

H05V-K, H03VV-F, H05VV-F, H05V2V2-F, H05Z1Z1-F, H05RN-F, H05BN4-F, H07RN-F

CURRENT CARRYING CAPACITY (Amperes):

Conductor Cross Sectional Area 1	Current Carrying Capacity	
	Single Phase a.c. 2	Three Phase a.c. 3
mm ²	A	A
0.5	3	3
0.75	6	6
1	10	10
1.25	13	-
1.5	16	16
2.5	25	20
4	32	25

VOLTAGE DROP (per Ampere per metre):

Conductor operating temperature: 60°C*

Conductor Cross Sectional Area 1	d.c. or Single Phase a.c. 2	Three Phase a.c. 3
mm ²	mV	mV
0.5	93	80
0.75	62	54
1	46	40
1.25	37	-
1.5	32	27
2.5	19	16
4	12	10

*NOTE: The tabulated values above are for 60°C rubber insulated and PVC-insulated flexible cords and for other types of flexible cords they are to be multiplied by the following factors:

For 90°C rubber or PVC insulated 1.09.

180°C rubber insulated 1.31.

GUIDE TO MINIMUM BENDING RADII ON FLEXIBLE CORDS AND CABLES

Cable Type	Cable Diameter (mm)			
	$\leq 8 \leq$	$> 8 \leq 12$	$> 12 \leq 20$	> 20
	M.B.R. (Minimum Bending Radius)			
Flexible Cable Thermoplastic (e.g. PVC)				
Fixed installation	3D	3D	4D	4D
Free movement*	5D	5D	6D	6D
Flexible Cable Elastomeric (e.g. rubber)				
Fixed installation	3D	3D	4D	4D
Free movement*	4D	4D	5D	6D

Where D = cable diameter.

The above values are based on recommendations given in BS7540 "Use of cables with a rated voltage not exceeding 450/750 V".

*These values do not apply to cables used on festoon, reeling drum, cranes, robotics, etc., where repetitive flexing and/or twisting is anticipated.

For further details refer to BS7540.