

[Close Window](#)

Eaton Environmental Monitoring Probe UPS Connectivity Device Technical Specs

Model	Environmental Monitoring Probe
Description	UPS accessory providing remote monitoring of temperature, humidity and two contact closure devices in combination with ConnectUPS Web Cards
Part Number	116750224-001
Protocol support	HTTP, SNMP, DHCP, bootp, ARP, RARP, Telnet, SMTP, TFTP, WAP
Web card compatibility	10/100Mb ConnectUPS-X, ConnectUPS-BD and ConnectUPS-E with FW V3.01 and higher
Network support	Ethernet 10/100 BaseT
Supported MIB	Eaton MIB, RFC1628 MIB
Network Client	Windows 9x, Windows XP, Windows 2000/NT, Novell, NetWare 4.x, 5.x and 6.0,
O/S supported for shutdown	UNIX, Compaq Tru64 4.x, 5.x, HP-UX 10.10, 10.20, 10.30, 11.00, IBM AIX 4.x (PowerPC), Linux with kernel 2.0 and higher (x86) and (AXP), SGI IRIX 6.x w/MIPS, Solaris 2.x, 8 (SPARC), Solaris 2.x, 8 with SunOS 5.6,7,8(x86), UnixWare 7.1 (x86 MacOS X (Darwin).
Temperature Monitoring	Measures temperatures between 0 and 80°C with an accuracy of +/-1°C
Humidity Monitoring	Measures relative humidity between 10 and 90% RH with an accuracy of +/-5%
Power input	Derives 12VDC from the Eaton Web/SNMP Card
Dimensions (LxWxH)	in 2.26 x 1.48 x 1.15 mm 57.6 x 37.6 x 29.3
Weight (lb/kg)	1.19 oz. (34 g)
Regulatory	FCC Class B, UL, CUL, CE

[Privacy Policy](#)
[Terms & Conditions](#)
[Copyright](#)

© 2013 Eaton
All Rights Reserved