

**Broadband Solutions****SVDC4P8TG****Directional Coupler, 8 dB, 4 port, terminating**

Environmental Specifications

Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Safety Standard	CE EN 60728-4 SCTE

Electrical Specifications Isolation

Isolation at Frequency Band, tap to tap	30.0 dB @ 5–15 MHz 30.0 dB @ 15–45 MHz 30.0 dB @ 50–300 MHz 27.0 dB @ 300–1002 MHz
---	--

Electrical Specifications

Power Passing	No
Impedance	75 ohm
Operating Frequency Band	5 – 1002 MHz
Insertion Loss at Frequency Band, tap	7.0 dB ±1.0 dB @ 5–550 MHz 7.0 dB ±1.0 dB @ 550–1002 MHz
Return Loss at Frequency Band, input, typical	20 dB @ 5–45 MHz 20 dB @ 50–1002 MHz
Return Loss at Frequency Band, output, typical	20 dB @ 5–45 MHz 20 dB @ 50–1002 MHz
Return Loss at Frequency Band, tap	21.0 dB @ 5–45 MHz 21.0 dB @ 50–1002 MHz
Spurious Signals/2nd Order Harmonics, before surge	<-60 dBmV
Shielding Effectiveness, minimum	120 dB
Surge Capability Test Method	ANSI/SCTE 81 Category A3 (6 kV, 200 A, Ring wave)
Surge Capability Waveform	100 KHz ring wave waveform

General Specifications

Device Type	Coupler
Mounting	Horizontal
Video Ports, quantity	4
Brand	HomeConnect®
Application	Indoor Outdoor
Warranty	Five years

Mechanical Specifications

Material Type	Zinc
---------------	------

Packed Dimensions

Carton Quantity	200
Height	215.90 mm 8.50 in
Length	482.60 mm 19.00 in
Width	368.30 mm 14.50 in

SVDC4P8TG

Shipping Weight 18.60 kg | 41.00 lb

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system