

**Contact**

Copper LAN Product Inquiry  
Phone: 717-354-6200  
berktek.support@nexans.com

## LANmark-1000 Enhanced Category 6 Patch

**LANmark-1000 Patch**

**Part Number:** 10032691

LANmark-1000 is an ANSI/TIA/EIA Enhanced Category 6 verified cable that is ideal for Gigabit Ethernet applications. Exceptional electrical characteristics include: PSNEXT, PAELFEXT, ELFEXT, RL and LCL/TCL/EL TCTL (balance). LANmark-1000 was the first cable in the industry which set requirements for cable balance. Cable balance helps protect the network from the damaging effects of outside noise sources.

### Description

#### Construction

24 AWG, stranded tinned copper wire insulated with polyethylene. Two insulated conductors twisted together to form a pair and four such pairs cabled to form the basic unit, jacketed with flame-retardant PVC.

### Standards

**International** ISO/IEC 11801

**National** ANSI/TIA-568-C.2; UL 444

#### Standards

North American: ANSI/TIA/EIA-568-C.2, UL 444 and C22.2 No. 214-02

International: ISO/IEC 11801-2nd Edition Category 6, UU Directive 2002/95/EC (RoHS)

#### Flame Rating

Patch-UL 1581, CM, IEC 332-1

UL Listed

#### Features

- Full power sum performance
- Documented balance characteristics (LCL, LCTL)
- ELT verified to ANSI/TIA/EIA-568-C.2

#### Benefits

- Optimal support for Gigabit Ethernet with headroom
- Power sum characterization gives highest performance for existing applications
- Addition of balance requirements improves overall cable performance and reduces transmission errors
- Characterized to 500 MHz, 250 MHz greater than the standard

## LANmark-1000 Enhanced Category 6 Patch

LANmark-1000 Patch

Part Number: 10032691

### Characteristics

<b>Construction characteristics</b>	
Type of cable	UTP
Colour	Violet
<b>Dimensional characteristics</b>	
Length per reel	1000.0 ft
Number of pairs	4
<b>Usage characteristics</b>	
Packaging	Reel
Field of application	Indoor
Category	Cat. 6
Fire safety	CM

### Technical Data - Physical

Technical Data - Physical			Color Code		
			Pair-1	White/Blue	Blue
Conductor	24 AWG Stranded Tinned Copper		Pair-2	White/Orange	Orange
Conductor diameter-in. (mm)	0.024	(0.61)	Pair-3	White/Green	Green
Insulated Conductor Diameter- in. (mm)	0.04	(1.02)	Pair-4	White/Brown	Brown
Cable diameter-in. (mm)	0.224	(5.69)			
Nominal cable weight-lb./kft. (kg/km)	25	(37)	<b>Temperature Rating</b>		
Max. installation tension-lb. (N)	25	(110)	Installation	0°C to +50°C	
Min. bend radius-in. (mm)	1	(25.4)	Operation	-20°C to +75°C	

### Parametric Measurements

<b>Mutual Capacitance</b>	4.4 nF/100 m nom., 5.6 nF/100 m max. @ 1 KHz
<b>DC resistance</b>	9.09 Ohms/100 m max.
<b>Skew</b>	25 ns/100 m nom, 30 nsec/100 m max.
<b>Pair to ground Unbalance</b>	330 pF/100 m max.
<b>Velocity of Propagation</b>	70% nom.
<b>Input Impedance</b>	100 ± 13% 0.772-100 MHz 100 ± [13+15log (F/100)] 100-350 MHz
<b>DC Resistance Unbalance:</b>	5% max.

### Technical Data - Electrical

FREQ MHz	SRL (dB)	RL (dB)	IL (dB/100m)	PS-NEXT (dB)	NEXT (dB)	ELFEXT (dB)	PS-ELFEXT (dB)	LCL/TCL (dB)	EL TCTL (dB)
	min.	min.	max.	min.	min.	min.	min.	min.	min.
1	26.0	20.0	2.4	73.3	75.3	68.8	65.8	50.0	35.0
4	26.0	23.6	4.6	64.3	66.3	56.7	53.7	43.0	22.0

## LANmark-1000 Enhanced Category 6 Patch

LANmark-1000 Patch

10	26.0	26.0	7.1	58.3	60.3	48.8	45.8	40.0	15.0
16	26.0	26.0	9.0	55.3	57.3	44.7	41.7	37.0	10.9
20	26.0	26.0	10.1	53.8	55.8	42.7	39.7	36.0	9.0
31.25	25.0	25.0	12.7	50.9	52.9	38.9	35.9	35.1	5.1
62.5	23.5	23.5	18.4	46.4	48.4	32.8	29.8	32.0	—
100	22.5	22.5	23.6	43.3	45.3	28.8	25.8	30.0	—
200	21.0	21.0	34.6	38.8	40.8	22.7	19.7	27.0	—
250	20.5	20.5	39.1	37.3	39.3	20.8	17.8	26.0	—
350	19.8	19.8	47.4	35.2	37.2	17.9	14.9	—	—
500	19.0	19.0	58.3	32.8	34.8	14.8	11.8	—	—

IMPORTANT: Berk-Tek performance guarantees are based on swept-frequency testing and apply to all frequencies for the entire specified frequency range and are not limited to the tables of data shown which are presented to demonstrate our guarantees at “representative” frequencies. Values above 350 MHz are provided for engineering information. Limited Combustible version also available. Other jacket colors available.

### Supported Category 6 Applications

STANDARD	APPLICATION	SPEED
IEEE 802.3	1000BASE-T	1 Gb/s
TIA/EIA-854	1000BASE-TX	1 Gb/s
ATM	155Mb/s	155 Mb/s
IEEE 802.3	100BASE-TX	100 Mb/s
CDDI		100 Mb/s
IEEE 802.3	10BASE-T	10 Mb/s
IEEE 802.3 af	PoE	1 Gb/s
IEEE 802.3 at	PoE+, Type 1 & 2	1 Gb/s

### Selling information

PLEASE NOTE: In the interest of product improvement, Berk-Tek, a Nexans company may make improvements or changes in the products, the programs or services described at any time without notice. Additionally, the information contained herein may include typographical errors or technical inaccuracies. Changes will be periodically made to address any such issues.