

Premises Distribution w/Armor-Tek Plenum Rated

24 x OS2 Premises Distribution Plenum Cable with Interlocking Armor

Part Number: PDPK024AB0707

Berk-Tek's Premises Distribution cable is a Plenum rated tight buffered design. Armor-Tek Interlocking Armor is wrapped around the Premises Distribution cable core. A plenum rated sheath is the extruded around the interlocking armor.

Description

Construction

- 900 µm buffered fibers surrounded by aramid yarns
- Sheathed using a special, state-of-the-art polymer material
- Aluminum and Steel interlock armor available
- OFCP Rated

Outdoor Considerations

Black jacketed and water-blocked versions of this plenum cable is available upon request for outdoor installations. Outdoor versions feature UV and fungus resistant jacketing.


Applications

Berk-Tek's tight buffered Interlocking Armor cable is intended for all high speed data applications including:

- 10BASE-FL
- 100BASE-SX/100BASE-FX
- ATM 155/ATM 622
- 1000BASE-SX/1000BASE-LX
- Fibre Channel 1.062/2.125
- 10GBASE-SR/SW
- 10GBASE-LX4
- 40/100 GbE

Features

- Single-mode, multimode, GIGAlite™ and hybrid designs available
- Available with new bend-optimized single-mode fibers
- High tensile strength, crush resistant
- Flexible, small diameter, 900 µm tight buffered construction core
- Six to 144 count fiber construction plenum designs ideal for horizontal and backbone and installations and along plenums
- Also available in low smoke zero halogen design
- Configurations available suitable for indoor/outdoor installations in conduit, below the frost line



Standards

International EN 50173; ISO/IEC 11801

National ANSI/ICEA S-83-596; ANSI/TIA-568-C.3; Telcordia GR-409

Premises Distribution w/Armor-Tek Plenum Rated

24 x OS2 Premises Distribution Plenum Cable with Interlocking Armor

Benefits

- Eliminates the need for conduit or plenum innerduct
- Significant cost savings in both materials and labor - up to 25%
- Accommodates last minute relocations or pathway changes
- Provides a higher concentration of cables in an area than conduit
- Can be installed in campus environments due to the durability and indoor/outdoor rating of the cable
- Armor provides crush protection and protection from rodent attacks
- Compliant to NFPA 130 (2010)

Characteristics

Construction characteristics	
Fiber optic type	SM (G.652D)
Type of cable	Tight Buffered (TB)
Outer sheath	Plenum
Sheath colour	Yellow
Armour type	Aluminum Interlock
Dimensional characteristics	
Number of optical fibres	24
Nominal outer diameter	0.584 in
Nominal outer diameter	14.8 mm
Approximate weight	123 lb/kft
Approximate weight	183 kg/km
Transmission characteristics	
Optical performance	AB (Single-mode, OS2)
Attenuation, max. 1310 nm (cabled)	0.7 dB/km
Attenuation, max. 1550 nm (cabled)	0.7 dB/km
Mechanical characteristics	
Maximum installation tension	150 lb
Maximum installation tension	667 N
Max. Load. Long Term (lbs)	45.0 lb
Max. Load. Long Term	200.0 N
Impacts per TIA/EIA FOTP-25	2 at 8.83 N-m
Crush resistance per TIA/EIA FOTP-41	440 N/cm
Cable flexibility per TIA/EIA FOTP-104	100 cycles
Usage characteristics	
Minimum Bending Radius - Install	8.8 in
Minimum Bend Radius - Install	22.3 cm
Minimum Bending Radius - LongTerm	5.8 in
Minimum Bending Radius - LongTerm	14.8 cm
Operating temperature, range	-20 .. 75 °C
Ambient installation temperature, range	0 .. 75 °C
Storage temperature, range	-40 .. 85 °C
Field of application	Indoor


Premises Distribution w/Armor-Tek Plenum Rated
24 x OS2 Premises Distribution Plenum Cable with Interlocking Armor

Standard Sheath Colors

Fiber Type	Core Size (um)	ISO-TIA Standard	Effective Modal BW @ 850 nm	Overfilled Launch BW @ 850 nm	Attenuation @ 850 nm	Attenuation @ 1300 nm	Attenuation @ 1550 nm	Sheath Color
AB	8.3	OS2	NS	NS	NS	0.7 dB/km	0.7 dB/km	Yellow
CB	62.5	OM1	200 MHz-km	200 MHz-km	3.5 dB/km	1.0 dB/km	NS	Orange
GB	62.5	OM1+	500 MHz-km	350 MHz-km	3.5 dB/km	1.0 dB/km	NS	Orange
ZB	50	OM2	500 MHz-km	500 MHz-km	3.5 dB/km	1.5 dB/km	NS	Orange
LB	50	OM2+	950 MHz-km	700 MHz-km	3.0 dB/km	1.0 dB/km	NS	Orange
EB	50	OM3	2000 MHz-km	1500 MHz-km	3.0 dB/km	1.0 dB/km	NS	Aqua
FB	50	OM4	4700 MHz-km	3500 MHz-km	3.0 dB/km	1.0 dB/km	NS	Aqua
XB	50	OM4+	4900 MHz-km	3675 MHz-km	3.0 dB/km	1.0 dB/km	NS	Aqua

NS = Not Specified

Cross-section Diagram - PDPK024



Manufacturing Release

IMPORTANT NOTICE: This product specification is provided for informational purposes only in order to illustrate typical product constructions, applications and/or methods of installation. Because conditions of actual installation and use are unique and will vary, Berk-Tek makes no representation or warranty as to the reliability, accuracy or completeness of this data, even if Berk-Tek is aware of the product's intended use or purpose. Furthermore, this data does not constitute, nor should it be regarded or relied upon, as professional engineering advice. Installation of cable should only be done by qualified personnel and in conformance with all safety, electrical and other applicable codes, standards, rules or regulations. Appropriate and correct product selection, installation and use, and compliance with all

Premises Distribution w/Armor-Tek Plenum Rated
24 x OS2 Premises Distribution Plenum Cable with Interlocking Armor

such codes, standards, rules and regulations, is a customer/end-user responsibility. Product specifications, standards, programs or services are subject to improvement or changes without notice. Berk-Tek accepts no liability for typographical errors, technical inaccuracies, omissions or misuse of the information contained herein. Changes will be periodically made to address any such issues.